



CODE QUIZ

February 2025

1. Per the 2022 CA Electrical Code, Section 300.5(E), direct-buried conductors or cables shall be permitted to be spliced or tapped without the use of splice boxes.
 - a. True
 - b. False
2. Per the 2022 CA Electrical Code, Section 406.9(C), receptacles shall not be installed within a zone measured ____feet horizontally and ____feet vertically from the top of the bathtub rim or shower stall threshold, unless the bathroom is not of sufficient size to include the required zone, then the receptacle shall be installed opposite the bathtub rim or shower stall threshold on the farthest wall within the room.
 - a. 2 feet, 6 feet
 - b. 3 feet, 8 feet
 - c. 5 feet, 8 feet
3. Per the 2022 CA Building Code, Section 1809.3, the top surface of footings shall be level. The bottom surface of footings shall be permitted to have a slope not exceeding ____unit vertical in ____units horizontal:
 - a. 1 unit vertical in 10 units horizontal
 - b. 1 unit vertical in 12 units horizontal
 - c. 1 unit vertical in 20 units horizontal
4. Per the 2022 CA Building Code, Section 1607.16, interior walls and partitions that exceed ____feet in height, including their finish materials, shall have adequate strength and stiffness to resist the loads to which they are subjected but not less than a horizontal load of 5 psf.
 - a. 4 feet
 - b. 6 feet
 - c. 7 feet
 - d. 8 feet
5. Per the 2022 CA Electrical Code, Section 422.16(B)(1)(1), the cord length for electrically operated in-sink waste disposers shall not be less than ____inches and not more than ____inches long.
 - a. 12 inches, 24 inches
 - b. 12 inches, 30 inches
 - c. 18 inches, 36 inches
 - d. 24 inches, 36 inches

Answer Key: 1: a 2: b 3: a 4: b 5: c

Please contact Ron Beehler by email at rbeehler@bpr-grp.com to discuss any questions.