



CODE QUIZ

August 2024

1. Per Section 505.2 of the 2022 California Building Code, the clear height above and below a mezzanine floor is:
 - a. 6'-8" above and 8'-0" below
 - b. 7'-0" above and 7'-0" below
 - c. 8'-0" below and 6'-8" above

2. Per Section R404.1.3.3.7.5 of the 2022 California Residential Code, for lap splices of horizontal and vertical concrete wall rebar reinforcement, the maximum gap between noncontact parallel bars at lap splices shall not exceed:
 - a. 2 inches
 - b. 6 bar diameters
 - c. The smaller of 1/5th the required lap length and 6 inches
 - d. 1/2 inch maximum

3. Per Section 604.10.1 of the 2022 CA Plumbing Code, an electrically continuous corrosion-resistant blue insulated tracer wire shall be installed adjacent to exterior underground plastic building supply piping. The tracer wire shall be not less than ___AWG, and the insulation type shall be suitable for direct burial.
 - a. 12
 - b. 14
 - c. 16

4. Per Section 503.1 of the 2022 California Building Code for the purpose of determining area limitations, height limitations and type of construction each portion of a building separated by one or more _____ shall be considered to be a separate building:
 - a. Fire barriers
 - b. Fire separations
 - c. Fire walls

5. According to the 2022 California Plumbing Code Section 719.1, Additional building sewer cleanouts shall be installed at intervals not to exceed 100 feet in straight runs and for each aggregate horizontal change in direction exceeding ____ degrees.
 - a. 45
 - b. 90
 - c. 135
 - d. 180

Answer Key: 1: b 2: c 3: b 4: c 5: c

Please contact Ron Beehler by email at rbeehler@bpr-grp.com to discuss any questions.