



## CODE QUIZ

### February 2024

1. Local jurisdictions may adopt ordinances to implement more restrictive requirements than those provided in Title 24. When a local jurisdiction adopts an ordinance to modify California Building Standards, express findings for each amendment, addition or deletion must be based on local climatic, topographical or geological conditions, and \_\_\_\_\_ conditions in the case of amendments to the California Green Building Standards Code.
  - a. Environmental.
  - b. Geotechnical.
  - c. Precipitation.
  - d. No additional justification is required for amendments to the California Green Building Standards Code.
  
2. California Building Standard Commission issues Supplements, (blue pages), for:
  - a. Approved additions to the codes.
  - b. Amendments to the codes.
  - c. Repeals to the codes.
  - d. Emergency building standards.
  - e. To correct non-substantive errors.
  - f. All the above.
  - g. a thru d above.
  
3. Per the California Board of Professional Engineers, Land Surveyors, and Geologists, Guide for City and County Officials, local agencies can require a geotechnical engineer to prepare geotechnical engineering documents rather than a civil engineer.
  - a. True
  - b. False
  
4. Per Section R702.2.2.2 of the 2022 California Residential Code, the finish coat for two coat cement plaster shall not be applied sooner than \_\_\_ hours after application of the first coat.
  - a. 24 hours
  - b. 48 hours
  - c. 72 hours
  
5. Per Section R502.4 of the 2022 California Residential Code, Double joists under parallel bearing partitions, that are separated to permit the installation of piping or vents, shall be full depth solid blocked with lumber not less than 2 inches in nominal thickness spaced not more than \_\_\_ feet on center.
  - a. 2 feet
  - b. 4 feet
  - c. 6 feet
  - d. 8 feet

*Answer Key: 1: a 2: g 3: b 4: b 5: b*

Please contact Ron Beehler by email at [rbeehler@bpr-grp.com](mailto:rbeehler@bpr-grp.com) to discuss any questions.