



CODE QUIZ

January 2024

1. Per Section 1011.2, Exception 3, of the 2022 California Building Code, where an incline platform lift or stairway chairlift is installed on stairways serving occupancies in Group R-3, or within dwelling units in occupancies in Group R-2, a clear passage width not less than _____ inches shall be provided.
 - a. 32 inches.
 - b. 30 inches.
 - c. 24 inches.
 - d. 20 inches.

2. Per Section 905.3 of the 2022 California Plumbing Code, unless prohibited by structural conditions, each vent pipe shall rise vertically to a point not less than _____ inches above the flood-level rim of the fixture served before offsetting horizontally.
 - a. 4 inches
 - b. 6 inches
 - c. 8 inches

3. Per Section 707.9 of the 2022 CA Plumbing Code, each cleanout in piping 2 inches or less in size shall be so installed that there is a clearance of not less than _____ inches by _____ inches in front of the cleanout.
 - a. 6 inches by 6 inches
 - b. 12 inches by 12 inches
 - c. 18 inches by 18 inches
 - d. 20 inches by 20 inches

4. Per Section 1804.4 of the 2022 CA Building Code, except for door landings or ramps, impervious surfaces within 10 feet a building foundation shall be sloped not less than _____ percent away from the building.
 - a. 2 percent
 - b. 5 percent
 - c. 8 percent

5. Per Section 202 of the 2022 California Existing Building Code “a _____ is a major activity for which the facility is intended”.
 - a. Occupancy Group
 - b. Primary Function
 - c. Proposed Use
 - d. Assigned Occupancy Group

Answer Key: 1: d 2: b 3: c 4: a 5: b

Please contact Ron Beehler by email at rbeehler@bpr-grp.com to discuss any questions.