



BPR
CONSULTING GROUP
CODE QUIZ
May 2023

1. Per Section 506.3.1 of the 2022 CA Building Code, to qualify for an area factor increase based on frontage, a building shall have not less than _____ percent of its perimeter on a public way or open space. Such open space shall be either on the same lot or dedicated for public use and shall be accessed from a street or approved fire lane.
 - a. 15 percent
 - b. 25 percent
 - c. 35 percent

2. Per Section 704.6.1 of the 2022 CA Building, where primary and secondary structural steel members require fire protection, any additional structural steel members having direct connection to the primary structural frame or secondary structural member shall be protected with the same fire-resistive material and thickness as required for the structural member for a distance of not less than _____ inches away from the structural member.
 - a. 6 inches
 - b. 12 inches
 - c. 18 inches

3. Per Section 510.2(4) of the 2022 CA Building Code, interior exit stairways within a Type 1A podium with a 3 hour fire-resistance-rated stairway enclosure and having Type III, IV, or V Construction above the Type 1A podium are permitted to be of _____ materials.
 - a. combustible
 - b. noncombustible

4. Per Section R310.2.1 of the 2022 CA Residential Code, the minimum net clear opening for grade floor emergency escape and rescue openings shall be _____ square feet.
 - a. 4.7 square feet
 - b. 5.0 square feet
 - c. 5.7 square feet

5. Per Section R310.3 of the 2022 California Residential Code, where a door is provided as the required emergency escape and rescue opening it shall be a side hinged door or a sliding door.
 - a. True
 - b. False

Answer Key: 1: B 2: B 3: A 4: B 5: A

Please contact Ron Beehler by email at rbeehler@bpr-grp.com to discuss any questions.