



CODE QUIZ

October 2023

1. Per Table R602.3(1) of the 2022 California Residential Code, 3/8 inch to 3/4-inch-thick wood structural panel roof sheathing shall be nailed to supporting roof framing members at ___ inches on center at supported edges, and at ___ inches on center at intermediate supports.
 - a. 6 inches, 12 inches.
 - b. 12 inches, 12 inches.
 - c. 6 inches, 6 inches.
 - d. 6 inches, 8 inches.
2. Per Section R903.4.1 of the 2022 California Residential Code, secondary overflow drains having the same size as the roof drains shall be installed with the inlet flow line located 2 inches above the low point of the roof, or overflow scuppers having _____ size of the roof drains and having a minimum opening height of 4 inches shall be installed.
 - a. Two times the size.
 - b. Three times the size.
 - c. The same size.
3. Per Section 202 of the 2022 California Green Building Standards Code, “a vehicle space with electrical panel space and load capacity to support a branch circuit and necessary raceways, both underground and/or surface mounted, to support EV charging”, is a:
 - a. Electrical Vehicle Ready Space.
 - b. Electric Vehicle Capable Space.
 - c. Electric Vehicle Charging Space.
4. Per Section 302.1 of the 2022 California Green Building Standards Code, live/work units, complying with the California Building Code, shall be considered mixed occupancies.
 - a. True
 - b. False
5. Per Subchapter 10, Multifamily Buildings Mandatory Requirements, Section 180.2(b)2Aiiia of the 2022 California Energy Code, for alterations to space conditioning system ductwork serving multifamily dwelling units, new ducts when installed in unconditioned spaces in Climate Zones 1, 2, 4, and 8 through 16, shall have a minimum R value of _____.
 - a. R-4
 - b. R-6
 - c. R-8
 - d. R-10

Answer Key: 1: c 2: b 3: b 4: b 5: c

Please contact Ron Beehler by email at rbeehler@bpr-grp.com to discuss any questions.