



CODE QUIZ

September 2023

1. Per Section 1020.5 of the 2022 California Building Code, a dead-end corridor shall not be limited in length where the length of the dead-end corridor is less than _____ times the least width of the dead-end corridor.
 - a. 1.5 times the least width.
 - b. 2.0 times the least width.
 - c. 2.5 times the least width.
 - d. 3.0 times the least width.

2. Per Section 402.7.2 of the 2022 California Building Code, atriums connecting _____ or more stories in a covered mall building shall be provided with a smoke control system.
 - a. Two
 - b. Three
 - c. Five

3. Per Section R404.1.1 of the 2022 California Residential Code, concrete or masonry foundation walls shall be designed in accordance with accepted engineering practices where which of the following conditions exist.
 - a. The distance from the bottom of the foundation to the top of the wall exceeds 48 inches.
 - b. The wall supports more than 48 inches of unbalanced backfill and does not have permanent lateral support at the top or bottom.
 - c. The wall is subjected to hydrostatic pressure from ground water.
 - d. The wall is not provided with positive drainage on the backfill side.
 - e. Both b and c.
 - f. Both a and d.

4. Per Section 403.1.6 of the 2022 California Residential Code, anchor bolts shall be permitted to be located while concrete is still plastic and before it has set.
 - a. True
 - b. False

5. Per Section R408 of the 2022 California Residential Code, ventilation openings through foundations or exterior walls surrounding under floor spaces where the ground surface is not covered by a Class 1 vapor retarder shall be located within ____ feet of each external corner of the under floor space.
 - a. Two feet
 - b. Three feet
 - c. Four feet
 - d. Six feet

Answer Key: 1: c 2: b 3: e 4: a 5: b

Please contact Ron Beehler by email at rbeehler@bpr-grp.com to discuss any questions.