



## **CODE QUIZ**

## March 2025

1.	load greater than 5,000 shall be classified as Risk Category
	a. I b. II c. III d. IV
2.	Per the 2022 CA Building Code, Section 1607.17, fixed ladders with rungs shall be designed to resist a single concentrated load of pounds in accordance with Section 4.5.4 of ASCE 7.
	<ul><li>a. 200 pounds</li><li>b. 250 pounds</li><li>c. 300 pounds</li><li>d. 350 pounds</li></ul>
3.	Per the 2022 CA Building Code, Section 1703.1.3, an approved special inspection agency shall employ experienced personnel
	<ul> <li>a. educated in conducting, supervising and evaluating tests and special inspections.</li> <li>b. who maintain current certifications for the special inspections that they perform.</li> <li>c. with the necessary training to conduct assigned tests and special inspections.</li> <li>d. all of the above.</li> </ul>
4.	Per the 2022 CA Green Building Standards Code, Nonresidential Mandatory Measures, Section 5.106.4.1.2, Long-term bicycle parking, for new buildings with tenant spaces that have 10 or more tenant-occupants, secure bicycle parking for percent of the tenant-occupant vehicular parking spaces is required with a minimum of one bicycle parking facility
	<ul><li>a. 5 percent</li><li>b. 10 percent</li><li>c. 20 percent</li></ul>
5.	Per the 2022 CA Electrical Code, Section 210.52, Dwelling unit receptacle outlets shall be installed in every kitchen family room, living room, parlor, library, den, sunroom, bedroom, recreation room or similar room or area of dwelling units such that no point measured horizontally along the floor line of any wall space is more than 6 feet from a receptacle outlet. Receptacle outlets in or on floors shall not be counted as part of the required number of receptacle outlets unless located within inches of the wall.
	<ul> <li>a. 12 inches</li> <li>b. 16 inches</li> <li>c. 18 inches</li> <li>d. 24 inches</li> </ul>