



## **BPR CODE QUIZ**June 2025

1.	pressure tests where the test pressure is 10 psi or less shall be performed with gauges with pressure graduations or increments of psi or less.  a. 0.10 psi b. 0.20 psi c. 0.25 psi d. 0.50 psi
2.	Per the 2022 CA Plumbing Code, Section 601.3, in buildings where potable and nonpotable water systems are installed, each system shall be clearly identified. Potable water systems shall be identified with signage with a  a. Blue background and white lettering. b. Green background and white lettering. c. White background and black lettering. d. White background and blue lettering.
3.	Per the 2022 CA Plumbing Code, Section 722.1, the sewer for an abandoned building shall be plugged or capped in an approved manner within of the property line.  a. 2 feet. b. 5 feet. c. 8 feet. d. 10 feet.
4.	Per the 2022 CA Building Code, Section 2407.1, glass used in a handrail or a guard shall be laminated glass constructed of fully tempered or heat-strengthened glass and shall be an approved safety glazing material. For all glazing types, the minimum nominal thickness shall be  a. 1/8 inch. b. 3/16 inch. c. 1/4 inch. d. 3/8 inch.
5.	Per the 2022 CA Residential Code, Section R602.3.1, utility grade studs shall not be spaced more than 16 inches on center, shall not support more than a roof and ceiling, and shall not exceed in height for exterior walls and load-bearing walls or for interior non load-bearing walls.  a. 8 feet, 10 feet.  b. 8 feet, 12 feet.  c. 9 feet, 10 feet.  d. 9 feet, 12 feet.