

POTABLE WATER

QUALPOL

Recommended Application

- Residential and commercial water service pipe.
- Well/pump water systems.

Raw Material

Manufactured using only virgin 4710 resin that meets or exceeds ASTM D3350.

Stocking Sizes

Available in 100, 300, and 500 foot coils.

Available Colors

Other colors available upon request.



SPECIFICATIONS

QualPol Potable Water Pipe meets or exceeds:

- ASTM D2239
- SDR9 / CTS PIPE AWWA C901
- NSF

		ASTM D2737	3/4"	1"	1 1/4"	1 1/2"	2"
250 PSI	SDR9 CTS	O.D.	0.875	1.125	1.375	1.625	2.125
		I.D.	0.681	0.875	1.069	1.263	1.653
		WALL	0.097	0.125	0.153	0.181	0.236
		WT/FT	0.103	0.170	0.254	0.353	0.602
		ASTM D2239	3/4"	1"	1 1/4"	1 1/2"	2"
250 PSI	SDR7	O.D.	1.06	1.349	1.774	2.070	2.657
		I.D.	0.824	1.049	1.380	1.610	2.067
		WALL	0.118	0.150	0.197	0.230	0.295
		WT/FT	0.152	0.246	0.424	0.578	0.952
200 PSI	SDR9	O.D.	1.008	1.283	1.686	1.968	2.527
		I.D.	0.824	1.049	1.380	1.610	2.067
		WALL	0.092	0.117	0.153	0.179	0.230
		WT/FT	0.116	0.190	0.320	0.430	0.710
160 PSI	SDR11.5	O.D.	0.968	1.231	1.620	1.890	2.427
		I.D.	0.824	1.049	1.380	1.610	2.067
		WALL	0.072	0.091	0.120	0.140	0.180
		WT/FT	0.090	0.143	0.246	0.335	0.544

946 W MAIN ST.
JEROME, ID 83338

(208) 324-1314