

# Hydrotech

## AIO Series Chemical Free Iron Filter

The AIO Chemical Free Iron filter is intended to be an effective and economical way to remove iron from water without the use of messy and dangerous chemicals or expensive pumps or an external venturi. The AIO valve uses a unique process to create an air bubble at the upper portion of the tank to oxidize any ferrous iron prior to being filtered by the media. It can also be used to remove low concentrations of dissolved hydrogen sulfide and manganese from water.

### How does the AIO (Air Induction Oxidization) filter work?

This filter works by adding oxygen to the incoming water by passing it through a bubble of compressed air. The water is then passed through a special filter bed. The special media not only increases the pH of the water to enhance iron removal but also acts as a physical barrier to trap iron precipitate. As more water passes through this iron filter, the oxygen in the unit is used up, and the media gets loaded with iron. The regeneration process then begins in order to replenish the supply of oxygen, and to backwash the precipitated iron trapped in the media bed. The iron removal efficiency will be more effective with high pH water. The filter is fitted with an inlet check valve to prevent any air from flowing backwards out of the filter tank.



Clean, Clear  
Iron-Free  
Water



| Model  | Media Cu Ft | Flow Rate USGPM |      |          | Mineral Tank Size | Pipe Size Inches | Ship Weight Lbs |
|--|-------------|-----------------|------|----------|-------------------|------------------|-----------------|
|  |             | Service         | Peak | Backwash |                   |                  |                 |
| <b>AIO (Air Induction Oxidizer) Chemical Free Iron Filter (Single Tank)</b>              |             |                 |      |          |                   |                  |                 |
| AIO75  | 0.75        | 2               | 4    | 3.5      | 8 x 44            | 3/4" - 1"        | 93              |
| AIO10  | 1.0         | 3               | 6    | 4        | 9 x 48            | 3/4" - 1"        | 120             |
| AIO15  | 1.5         | 4               | 10   | 5        | 10 x 54           | 3/4" - 1"        | 164             |
| AIO20  | 2.00        | 5               | 12   | 7        | 1252              | 3/4" - 1"        | 207             |
| AIO30  | 3.00        | 6               | 14   | 10       | 1465              | 3/4" - 1"        | 330             |
| AIO75M   | 0.75        | 2               | 4    | 3.5      | 8 x 44            | 3/4" - 1"        | 93              |
| AIO10M   | 1.0         | 3               | 6    | 4        | 9 x 48            | 3/4" - 1"        | 120             |
| AIO15M   | 1.5         | 4               | 10   | 5        | 10 x 54           | 3/4" - 1"        | 164             |
| AIO20M   | 2.00        | 5               | 12   | 7        | 1252              | 3/4" - 1"        | 207             |
| AIO30M   | 3.00        | 6               | 14   | 10       | 1465              | 3/4" - 1"        | 330             |
| <b>AIOC (Air Induction Oxidizer) Filter For Hydrogen Sulfide Reduction (Single Tank)</b> |             |                 |      |          |                   |                  |                 |
| AIOC75   | 0.75        | 2               | 4    | 3.5      | 8 x 44            | 3/4" - 1"        | 50              |
| AIOC10   | 1.0         | 3               | 6    | 4        | 9 x 48            | 3/4" - 1"        | 60              |
| AIOC15   | 1.5         | 4               | 10   | 5        | 10 x 54           | 3/4" - 1"        | 78              |
| AIOC20   | 2.00        | 5               | 12   | 7        | 1252              | 3/4" - 1"        | 95              |
| AIOC30   | 3.00        | 6               | 14   | 10       | 1465              | 3/4" - 1"        | 138             |
| <b>AIOB (Air Induction Oxidizer) Birm Iron Filter</b>                                    |             |                 |      |          |                   |                  |                 |
| AIOB75   | 0.75        | 2               | 4    | 3.5      | 8 x 44            | 3/4" - 1"        | 67              |
| AIOB10   | 1.0         | 3               | 6    | 4        | 9 x 48            | 3/4" - 1"        | 79              |
| AIOB15   | 1.5         | 4               | 10   | 5        | 10 x 54           | 3/4" - 1"        | 101             |
| AIOB20   | 2.00        | 5               | 12   | 7        | 1252              | 3/4" - 1"        | 121             |
| AIOB30   | 3.00        | 6               | 14   | 10       | 1465              | 3/4" - 1"        | 184             |

**Options:**

- Pressure tanks in black, blue or natural
- Tank jackets with black caps in chrome, grey, blue or vanilla



**565 valve**

- Simple user friendly 2 line /32 character display
- Rotating 'No Touch' Information Display (i.e. Date last regenerate, volume remaining)
- Seven Year Warranty



**765 valve**

- Simple electronics with index knob to manually initiate regeneration and select cycle position
- Five Year Warranty



**89 valve**

- True 1" porting for high flow rates up to 18" systems. Ideal for larger homes.
- Large Backlit LCD display screen with 4 line / 80 character touch pad screen.
- Seven Year Warranty



**Hydrotech**

**Toll Free: 1-877-288-9888**  
**www.hydrotechwater.com**

Regina, SK • Cambridge, ON • Carmel, IN • Fridley, MN •  
 Phoenix, AZ • Pottstown, PA

Your Local Water Treatment Professional

**Bay Lakes EcoWater Systems**  
**Serving Northeastern Wisconsin**  
**920-794-7077 \* 920-684-6819**  
**920-469-5510 \* 920-746-9191**  
**1-800-242-7770**

