





## CAPACITIES

<p>Standard Equipments</p> 	<b>PUNCHING</b>	<b>HKM 40</b>
	Diameter x max. thickness	Ø 22 x 15 mm
	Diameter x thickness	Ø 30 X 10 mm
	Maximum diameter	Ø 38 X 8 mm
	Stroke	50 mm
	Stroke count in (20 mm)	x 20
	Throat depth	175 mm
	Working height	970 mm
<p>Standard Equipments</p> 	<b>STEEL BAR SHEAR</b>	<b>HKM 40</b>
	Round / Square	Ø 30 - 25 mm
<p>Standard Equipments</p> 	<b>ANGLE SHEAR</b>	<b>HKM 40</b>
	Angle section (90°)	80 x 80 x 8 mm
	Angle section (45°)	50 x 6 mm
	Working height	1110 mm
<p>Standard Equipments</p> 	<b>SHEET METAL SHEAR</b>	<b>HKM 40</b>
	Sheet metal	200 x 13 mm
	Sheet metal	300 x 6 mm
	Blade length	356 mm
	Shearing with angle	80 x 10 mm
	Working height	980 mm
<p>Standard Equipments</p> 	<b>NOTCHING</b>	<b>HKM 40</b>
	Thickness	
	Width	
	Depth	
	Working height	



## CAPACITIES

Optional Equipments	OPTIONAL TOOLS	HKM 40
	U - I section blades (for UPN - IPN cutting)	76 X 38 mm  38 X 6 mm
	Special V - notching tooling	
	V - bending press brake Bar bend max.	
	V - bending press brake Sheet bend. max.	
	Punching on notcher Throat depth	
	Punching on notcher Max. capacity	
	<b>TECHNICAL DATA</b>	<b>HKM 40</b>
	Motor power	3kW
	Weight	580 kg
	Machine Dimensions (L x W x H)	1100 x 800 x 1520 mm
		40 ton

