

Xperience3

Experience the Comfort



www.carriercca.com

Carrier

turn to the experts™





turn to the experts™



Xperience3

- Compact design
- Multi position
- Auto-swing in both directions
- Auto-cool-dry-heat-fan
- 3 speed fan
- On/off timer
- Left or right drain pipe connection
- Wireless remote control
- R410A /R22 refrigerant

TECHNICAL SPECIFICATIONS					
Model #			42KUE036N	42KUE048N	42KUE060N
Power Supply		V-ph-Hz	208-230V~ 60Hz, 1Ph	208-230V~ 60Hz, 1Ph	208-230V~ 60Hz, 1Ph
Nominal Capacity		Btu/h	36000	48000	60000
Indoor Air Flow (Hi/Med/Lo)		m ³ /h	1800/1600/1350	2300/1900/1700	2300/1900/1700
Indoor Noise Level (Hi/Mi/Lo)		dB(A)	55/51/48	58/53/49	58/53/49
Indoor Unit	Dimension (W x D x H) (body)	mm	1285x675x235	1650x675x235	1650x675x235
	Packing (W x D x H) (body)	mm	1360x755x313	1725x755x313	1725x755x313
	Net/Gross weight (body)	Kg	32/37	42/48	42/48
Refrigerant piping	Liquid side/ Gas side	mm(inch)	Φ9.52/Φ19 (3/8"3/4")	Φ9.52/Φ19 (3/8"/3/4")	Φ9.52/Φ19 (3/8"/3/4")



turn to the experts® 

STANDARD EFFICIENCY - SINGLE PHASE

			36K	48K	55K
Sale model			38KUA03631010	38KUA04831010	38KUA06031010
Power supply	V-Ph-Hz		220V, 1Ph, 60Hz	220V, 1Ph, 60Hz	220V, 1Ph, 60Hz
Max. input consumption	W		54000	65000	7625
Max. current	A		25.5	30.7	34.6
Outdoor air flow	m ³ /h		4500	7400	7600
Outdoor noise level (sound pressure)	dB(A)		64.5	65.0	65.7
Outdoor unit	Dimension (W*D*H)	mm	600x600x759	710x710x759	710x710x759
	Packing (W*D*H)	mm	628x628x794	738x738x794	738x738x872
	Net/Gross weight	kg	57.8/61.4	71.8/76.1	80.0/85.0
Refrigerant	Type		R410A	R410A	R410A
	Charge volume	kg	1.9	2.20	2.20
Design pressure	MPa		4.2/1.5	4.2/1.5	4.2/1.5
Refrigerant piping	Liquid side/Gas side	mm	Φ9.52/Φ19(3/8"/3/4")	Φ9.52/Φ19(3/8"/3/4")	Φ9.52/Φ19(3/8"/3/4")
	Max. refrigerant pipe length	m	30	50	50
	Max. difference in level	m	20	30	30
Ambient temperature	Cooling	°C	18-43	18-43	18-43
	Heating	°C			
Qty' per 20' /40' /40'HQ					



Authorized Dealer