



Flexible Machine Products Ltd

## PVC Hoses, Polyurethane

### PVC Unreinforced Clear Tube

Clear Hose suitable for use in Industrial and Food Environments.

PVC material has FDA, BGA and BPF/ BIPRA approval.

Temperature: -20°C to +55°C



**Supplied in 30 Metre coils – Other colours available on request**

Size	Description	Part Number
3/16"	5mm x 8mm PVC Clear	P010508
1/4"	6mm x 9mm PVC Clear	P010609
5/16"	8mm x 11mm PVC Clear	P010811
3/8"	9mm x 12mm PVC Clear	P010912
1/2"	12mm x 15mm PVC Clear	P011215

### Unreinforced Polyurethane Tube

Clear Tube ideal for Chemicals and Fuels

Remains Flexible at Low Temperatures

Temperature: -30°C to +70°C  
(occasional use - 100°C)



Size	Description	Part Number
1/4"	6mm x 9mm Polyurethane - 30m	P020609
5/16"	8mm x 11mm Polyurethane - 30m	P020811

### PVC Reinforced Clear Hose

Reinforced Clear Hose suitable for use in Industrial and Food Environments.

PVC material has BGA and BIPRA approval.

Chemical Resistance to most oxidising and reducing agents, dilute acids and alkalis

Pressure: 20°C with 3:1 Safety. Temperature : -20°C to 55°C

**Supplied in 30 Metre coils**

**Other colours available on request**



Size	W/P Bar	Description	Part Number
3/16"	20	Reinforced PVC	P200510
1/4"	17	Reinforced PVC	P200612
5/16"	16	Reinforced PVC	P200814
3/8"	16	Reinforced PVC	P201016
1/2"	14	Reinforced PVC	P201219
5/8"	11	Reinforced PVC	P201623
3/4"	9	Reinforced PVC	P201926
1"	7	Reinforced PVC	P202533



Flexible Machine Products Ltd

## Industrial Hoses

### Water Hose Pressure 15- 20 Bar Temperature 70°C

Black Cover,  
Reinforcement Textile Cord

Ideal for Inlet Hose,  
Wash Down and General  
Industrial Applications



Size	Description	Part Number
1/2"	Water / Air Hose 15 Bar Black	H011215
3/4"	Water / Air Hose 15 Bar Black	H011915

### Saturated Steam Wash Down Hose Pressure 17 Bar Temperature 208°C

Red Cover, Reinforcement  
with High Tensile Steel Cords

Specification : BS5342/2  
Class A - DIN 2825 -  
NFT 47263  
CAT 1 TYPE 3



Hose for Steam use should be fitted with  
bolt on Steam Couplings available on request.

Size	Description	Part Number
1/2"	Wash Down Hose 17 Bar Red	H071217
3/4"	Wash Down Hose 17 Bar Red	H071917

### PVC Suction and Delivery Hoses

#### Transparent Plasticised PVC with Steel Wire Helix Reinforcement

Pressure : 5 - 7 Bar  
Vacuum : 85%  
Temperature : -5°C to +60°C



Size	Description	Part Number
1/2"	PVC Suction Hose Wire Helix	P371201
3/4"	PVC Suction Hose Wire Helix	P371901
1"	PVC Suction Hose Wire Helix	P372501

### Water Hose Pressure 20 Bar Temperature 185°C

Yellow Cover - Rein-  
forcement High Tensile  
Textile Cords

Ideal for Heavy Duty  
Inlet Hose, Wash Down  
and General Industrial  
Applications



Size	Description	Part Number
1/2"	Water / Air Hose 20 Bar Yellow	H011215
3/4"	Water / Air Hose 20 Bar Yellow	H011915

### FDA Steam / Hot Water Wash Down Hose Temperature 165°C

Blue Cover, for use in  
Food Factories Etc  
Water : 15 Bar  
Steam : 7 Bar

For use with Hot Water and  
Saturated Steam.



Size	Description	Part Number
1/2"	Wash Down Hose 15 Bar Blue	H061215
3/4"	Wash Down Hose 15 Bar Blue	H061915
1"	Wash Down Hose 15 Bar Blue	

#### Green Transparent Plasticised PVC with Rigid PVC Helix Reinforcement

Pressure : 7 Bar  
Vacuum : 60%  
Temperature :  
5°C to +60°C



Size	Description	Part Number
3/4"	Green Tint PVC Suction Hose	P361901
1"	Green Tint PVC Suction Hose	P362501