



**Old Western Paint Co., Inc.**

2001 W. Barberry Pl.  
Denver, CO 80204  
Phone: 303-825-5147  
www.oldwesternpaint.com

*Made in Colorado, for Colorado's Climate!*

# Colorado Pro 600

*Interior Production Primers*  
0605 First-Coat Drywall Primer

## Description

Colorado Pro 600 First-Coat Drywall Primer 0605 is an excellent 1<sup>st</sup> coat drywall primer designed for new interior drywall. It seals bare drywall and helps cover seems and joints, while providing a smooth, uniform surface for texture and paint. The lower viscosity allows it to be sprayed more easily than similar products, making it ready-to-use straight out of the container. Ideal for new-home construction, multi-family construction, commercial construction, or anywhere where new drywall is installed.

## Application and Substrate Information

Mix or stir thoroughly before using. Paint should be applied using airless spray equipment (2,000 psi, 0.015" – 0.021" tip). If desired, a second coat may be applied 1-2 hours after applying the first coat as drying conditions allow.

Recommended for properly prepared gypsum board and drywall. See General Surface Preparation for further details.

For best results, temperatures (air, surface and material temperatures) should be between 50°F – 90°F (10°-32°C) before applying.

## Product Data

Gloss/Sheen (85°)	< 5
VOC Content (g/L)	< 10
Viscosity (Krebs Units)	83 (± 3)
Density (lb/gal)	11.6
Weight Solids	44 %
Volume Solids	25 %
Coverage (4 mil wet)	400 ft <sup>2</sup> *

\*Theoretical value; may vary based on substrate porosity/application method

## Features and Benefits

- ✓ Formulated and made in Colorado
- ✓ Very low VOC
- ✓ Helps hide seems and joints
- ✓ Lower viscosity makes it easy to spray
- ✓ Good hide and brightness

## Thinning

This product is designed to not require thinning. If thinning is desired, a small amount of water may be used.

## Dry Time

Will dry to touch in one hour or less; may be recoated after 1 to 2 hours. Dry time may be affected by poor ventilation, low temperatures, amount of colorant and/or high humidity areas.

## Clean-up

Clean all tools and equipment with warm, soapy water.

## Environmental/Health Considerations

Formulated without lead, mercury, and other heavy metals. Does not contain ethylene glycol. No reportable amount of crystalline silica.



*Made in Colorado, for Colorado's Climate!*



## Old Western Paint Co., Inc.

2001 W. Barberry Pl.  
Denver, CO 80204  
Phone: 303-825-5147  
[www.oldwesternpaint.com](http://www.oldwesternpaint.com)

### General Surface Preparation

All foreign material, including loose or peeling paint, dirt, grease, oil, wax, chalk, mildew, rust, dust, curing agents, etc., must be removed prior to use. Failing to do so may compromise proper adhesion and overall performance. Caulk all cracks and open seams. Putty all nail holes. Rough or patched surfaces should be sanded.

### Specific Substrate Recommendations

**Siding:** Not recommended for exterior application.

**Concrete/Masonry Block:** Not recommended for concrete.

**Metal:** Not recommended for metal substrates.

**Drywall/Gypsum Board:** Nails and screws should be countersunk and properly covered using putty or drywall mud, then sanded to be flush with the rest of the surface.

**Wood:** Not recommended for wood surfaces.

### Packaging

Available in 5-gallon containers. Actual volume amounts of paint are indicated on the label. Volume is adjusted to account for the addition of colorants.

### Intended Use

To be used in a manner consistent with latex wall paints and finishes. Do not take internally. Keep out of reach of children and pets. Not recommended for floors or where water can puddle. Keep from freezing.

**WARNING:** If you scrape, sand or remove old paint, you may release lead dust. LEAD IS TOXIC AND MAY CAUSE SERIOUS ILLNESS IF YOU ARE EXPOSED, ESPECIALLY FOR CHILDREN OR THOSE WHO ARE PREGNANT. Wear a properly fitted NIOSH-approved respirator and prevent skin contact to minimize lead exposure. Clean up carefully with a HEPA vacuum and a wet mop. For further information, contact the U.S.E.P.A. National Lead Information Hotline at 1-800-424-LEAD or visit [www.epa.gov/lead](http://www.epa.gov/lead).

### Disclaimer

All information and data appearing in this document are provided in good faith and are believed to be reliable and accurate to the best of our knowledge at the date of publication. None of the provided information is to be considered a warranty or quality specification or all-inclusive and is given only as a guidance. It is the user's responsibility to determine the intended utilization of the product. No guarantee, expressed or implied, is made by Old Western Paint Co., Inc. And the user assumes all risk and responsibility.