



ELEVATION

Made in Colorado, for Colorado's Climate!

Elevation

**Premium 100% Acrylic Finishes
1215, 1216 Solid Cover Latex Stain**

Description

Elevation 100% Acrylic Solid Cover Latex Stain is a premium, 100% acrylic solid body stain that is formulated specifically to endure the rigors of Colorado's unique climate. When fully cured, it resists moisture, chalking, and fading due to intensified UV exposure in many of Colorado's high altitude environments. Recommended for wood or concrete vertical substrates. Developed and manufactured in Denver, Colorado, *Elevation 100% Acrylic Solid Cover Latex Stain* is the ideal choice for Colorado's most challenging environments, both indoors and out.

Application and Substrate Information

Mix or stir thoroughly before using. Product should be applied using brush, roller, or through airless spray equipment (2,000 psi, 0.015" – 0.021" tip). A second coat may be applied at a minimum of 3-4 hours after applying the first coat as drying conditions allow.

For best results, temperatures (air, surface and material temperatures) should be at or above 35°F (2°C) and at least 5°F above the dew point before applying. These conditions must remain at or above these levels for at least 8 hours (longer for deeper colors). Do not apply if condensation is expected within 4-6 hours of applying.

Old Western Paint Co., Inc.

2001 W. Barberry Pl.
Denver, CO 80204
Phone: 303-825-5147
Fax: 303-825-2437
www.oldwestpaint.com

Product Data

Gloss/Sheen (85°)	< 5 units
VOC Content (g/L)	< 100
Viscosity (Krebs Units)	86 (± 3)
Density (lb/gal)	10.8
Weight Solids	47 %
Volume Solids	31.5 %
Coverage (1.5 dry film)	350 ft ² *

*Theoretical value; may vary based on substrate porosity/application method

Features and Benefits

- ✓ Designed specifically for Colorado's Climate
- ✓ Excellent hiding power
- ✓ Provides a rich, solid body appearance
- ✓ Designed for wood or concrete
- ✓ Available in any color using CPC's no-VOC containing colorants

Thinning

Thinning is not required, though a small amount of water can be added if desired. Thinned paint is more prone to in-can settling and biological contamination if not used immediately and/or stored over long periods of time.

Dry Time

Will dry to touch in one hour or less; may be recoated after four hours. Typical time for full cure is 7 days. Dry time may be affected by poor ventilation, low temperatures, amount of colorant and/or high humidity areas.

Clean-up

Clean all tools and equipment with warm, soapy water.

Environmental/Health Considerations

Formulated without lead, mercury, and other heavy metals. Does not contain ethylene glycol. No reportable amount of crystalline silica.



ELEVATION

Old Western Paint Co., Inc.

2001 W. Barberry Pl.
Denver, CO 80204
Phone: 303-825-5147
Fax: 303-825-2437
www.oldwesternpaint.com

Made in Colorado, for Colorado's Climate!

General Surface Preparation

All foreign material, including loose or peeling paint, dirt, grease, oil, wax, chalk, mildew, rust, dust, curing agents, etc., must be removed prior to use. Failing to do so may compromise proper adhesion and overall performance. Caulk all cracks and open seams. Putty all nail holes. An appropriate primer should be used when coating bare or porous substrates. A stain blocking primer is recommended over areas where stains would 'bleed through' to the surface. Glossy surfaces should be dulled prior to coating, and rough or patched surfaces should be sanded.

Specific Substrate Recommendations

Siding: May be used over wood or concrete siding, including composite siding. Not recommended for vinyl siding.

Concrete/Masonry Block: New concrete should cure for at least 30 days prior to applying. The surface pH should be below 10 before applying an alkali resistant primer. Block filler should be used over masonry block.

Metal: Ferrous metal should be primed with a waterborne or solventborne rust resistant metal primer. Non-ferrous metal and zinc treated metal should be primed with an all-purpose metal primer.

Drywall/Gypsum Board: Not recommended. A flat finish such as Colorado Pro 600 Flat, Colorado Pro 700 Flat, or Elevation 1260 flat is recommended for these substrates.

Wood: Unpainted wood should be sanded smooth, wiped, and primed with an appropriate primer. For redwood or cedar, a stain blocking primer may be required, especially for lighter stain colors.

Packaging

Available in 1-gallon and 5-gallon containers. Actual volume amounts of paint are indicated on the label. Volume is adjusted to account for the addition of colorants.

Intended Use

To be used in a manner consistent with latex wall paints and finishes. Do not take internally. Keep out of reach of children and pets. Not recommended for floors or where water can puddle. Keep from freezing.

WARNING: If you scrape, sand or remove old paint, you may release lead dust. LEAD IS TOXIC AND MAY CAUSE SERIOUS ILLNESS IF YOU ARE EXPOSED, ESPECIALLY FOR CHILDREN OR THOSE WHO ARE PREGNANT. Wear a properly fitted NIOSH-approved respirator and prevent skin contact to minimize lead exposure. Clean up carefully with a HEPA vacuum and a wet mop. For further information, contact the U.S.E.P.A. National Lead Information Hotline at 1-800-424-LEAD or visit www.epa.gov/lead.

Disclaimer

All information and data appearing in this document are provided in good faith and are believed to be reliable and accurate to the best of our knowledge at the date of publication. None of the provided information is to be considered a warranty or quality specification or all-inclusive and is given only as a guidance. It is the user's responsibility to determine the intended utilization of the product. No guarantee, expressed or implied, is made by Old Western Paint Co., Inc. And the user assumes all risk and responsibility.