



OLD WESTERN PAINT CO., INC
2001 West Barberry Place
Denver, Colorado 80204

Phone: 303-825-5147

Toll Free: 888-765-9827

www.oldwesternpaint.com

PRODUCT INFORMATION

POLY VAR CONJUGATED OIL VARNISH

LV1255-02 Satin, LV1256-04 Velvet, LV1255-50 Gloss, LV1267-50 Gloss Gym

TYPE: One packaged oil modified pure 100% polyurethane.

DESCRIPTION: *POLY VAR POLYURETHANE* is a clear, durable interior floor finish available in Gloss, Semi Gloss, Velvet and Satin Sheen. For use on all wood floors, terracotta tile and concrete floors.

CLEAN UP: Mineral Spirits/paint thinner

APPLICATION:

Brush, Spray, Wool pads – Stir thoroughly. Surface should be free from dust, dirt, wax, grease, oily residue, peeling paint or any loose substance.

Old Floors - Old floors should be abraded. After abrading, remove all dust by vacuuming and tacking. Be sure the floor is dry before coating. Apply finish, two or three coats, allowing them to dry between coats and abrading between coats.

New Floors – Sand floor thoroughly using NOFMA accepted methods. Remove all dust by vacuuming and tacking. Be sure the floor is dry before applying 3 coats of finish. Abrade, clean and tack between coats.

Finish will adhere to most stains and finishes with proper preparation and complete drying. However, ALWAYS PREPARE A SAMPLE/TEST AREA TO DETERMINE COMPATABILITY.

SPREADING RATE: Theoretical coverage 500-550 square feet per gallon, subject to surface porosity, texture and application method.

DRYING TIME: Dries in 2-4 hours (dust free), recoat in 12 hours. Drying time may be affected by excessive humidity, low temperature, failure of air movement and thickness of finish.

ANALYSIS:

SOLIDS BY WEIGHT

LV1255-02 Satin	42.00%
LV1256-04 Velvet	42.00%
LV1255-50 Gloss	50.00%

LV1267-50 Gloss Gym Finish	50.00%
----------------------------	--------

SOLIDS BY VOLUME

LV1255-02 Satin	34.00%
LV1256-04 Velvet	34.00%
LV1255-50 Gloss	43.00%

LV1267-50 Gloss Gym Finish	43.00%
----------------------------	--------

SOLVENT TYPE Aliphatic

PENCIL HARDNESS 2H

GLOSS 60 DEGREE

LV1255-02 Satin	28-34
LV1256-04 Velvet	34-40
LV1255-50 Gloss	95-97

LV1267-50 Gloss Gym Finish	95-97
----------------------------	-------

V.O.C. content

LV1255-02 Satin	504 grams/liter, 4.20 lbs/gal
LV1256-04 Velvet	504 grams/liter, 4.20 lbs/gal
LV1255-50 Gloss	444 grams/liter, 3.71 lbs/gal
LV1267-50 Gloss	444 grams/liter, 3.71 lbs/gal

Features:

- ❖ Superior Quality
- ❖ 100% Polyurethane Resin
- ❖ Excellent Flow and Level
- ❖ Made in the U.S.A.

LIMITED WARRANTY if used as directed, including proper application and surface preparation in accordance with label directions, this product is warranted to be free from defect when used for its intended application for a period of one year from the date of purchase. This limited warranty does not apply if the product is mixed with any other ingredient. Buyer assumes all risks of handling. Buyer assumes all risks of handling. Buyer's sole and exclusive remedy with respect to any defective product is replacement of product or refund of the purchase price, at Manufacturer's sole option and only after receipt of proof of purchase. THIS LIMITED WARRANTY IS EXCLUSIVE AND IN LIEU OF ALL OTHER WARRANTIES, EXPRESS, IMPLIED OR STATUTORY, INCLUDING WARRANTIES OF MERCHANTABILITY AND FITNESS FOR A PARTICULAR PURPOSE AND DESIGN. IN NO EVENT SHALL MANUFACTURER BE LIABLE FOR ANY INCIDENTAL OR CONSEQUENTIAL DAMAGES OR LABOR COST. Some states do not allow limitations on how long an implied warranty lasts or the exclusion or limitation of incidental or consequential damages, so the above limitations or exclusions may not apply to you. This warranty gives you specific legal rights, and you may also have other rights which vary from state to state.