

# ROCKWOOL Safe'n'Sound® for Floors and Ceilings

The new 6" thick stone wool batt insulation makes installation in ceilings between floors quicker and easier.

## Features and Benefits

- Designed specifically for sound dampening to help prevent noise travelling from one floor to the next – providing a quieter, more comfortable home
- Friction fit between floors in a single layer, simplifying the process for greater efficiency - reducing installation time
- Non-combustible with a melting point of approximately 2150°F (1177°C)
- Water and moisture resistant - does not absorb moisture to maintain insulating value
- Does not rot or promote the growth of fungi or mildew
- GREENGUARD Gold certified - receiving the highest designation for indoor air quality



## SKU Profile

Product Number	Stud type	Thickness	Width	Length	Coverage	Classification (minimum order qty.)
292897*	16" Wood	6 in. (152.4 mm)	15 1/4 in. (387 mm)	47 in. (1194 mm)	29.9 ft. <sup>2</sup> (2.78 m <sup>2</sup> )	STD (1 pallet)
292908	24" Wood	6 in. (152.4 mm)	23 in. (584 mm)	47 in. (1194 mm)	30 ft. <sup>2</sup> (2.79 m <sup>2</sup> )	NSK (13 pallets)
307614*	16" I-Joist	6 in. (152.4 mm)	16 1/4 in. (412.7 mm)	48 in. (1219 mm)	32.5 ft. <sup>2</sup> (3.01 m <sup>2</sup> )	STD (1 pallet)
292903	19.2" I-Joist	6 in. (152.4 mm)	19 1/5 in. (487.7 mm)	47 in. (1194 mm)	31.3 ft. <sup>2</sup> (2.91 m <sup>2</sup> )	NSK (12 pallets)

\* Western customers (BC, AB, WA, OR) please use Product Number 292904 for 16" wood size.

\*For 16" I-Joist size use Product Number 307616.

### ROCKWOOL

8024 Esquesing Line  
Milton, ON L9T 6W3  
Tel: 1 800 265 6878  
[www.rockwool.com/safensound](http://www.rockwool.com/safensound)

