

2026 Lawn Mower Modstock

Twisted Metal Motorsports

Any questions must be approved by the head inspector () either call or text

There aren't many rules because you can only do these things!!

You must pass inspection within 2 times through inspection or you will not be permitted to run.

After your mower has been inspected or flagged there will be no refunds.

We are not responsible for any accidents or injuries!

You are only permitted to have 2 fires. This will result in a disqualification.

If your helmet comes off you're out.

If you intentionally flip a competitor you're out of the competition.

If you flip on your side or over and any part of your body touches the ground you're out of the competition.

- 1- Mower must be a factory-available lawn mower. (No homemade frames)
- 2- No rear engine lawn mowers allowed.
- 3- Must be a factory lawn mower engine such as Briggs & Stratton, Kohler, Tecumseh, Onan, etc.
- 4- Transaxles must be factory-available lawn mower transaxles but any reinforcing and/or welding of spider gears may be permitted.
- 5- All lawn mowers must have good working brakes at the start of the heat.
- 6- Gas tanks must be secured and have a cap on them. Must run an on/ off shut off for safety if leaking you will be asked to shutdown.
- 7- Frame modifications are allowed. You can have 2x2 1/4 max tubing or plate from front of frame to beginning of foot pan.. rear section of frame from back of foot rest to end of frame can have 2x2 1/4 thick max tubing or plate. If you have full tubing front to back you will be asked to cut.
- 8- Engine bay reinforcement is permitted under the hood. You may use 2x2 1/4 max tubing from front plate to leg guards as a "kicker" you must be able to hit the front tire. If abused you will lose it.
- 9- Leg guards must be within factory body lines. Welded or bolted from foot rest to rear fenders. You are allowed belly bars but must not connect to the frame.
- 10- NO FRONT BUMPERS. You may have a rear bumper but must be within the inside of back tires.
- 11- Must run factory hood of lawn mower if hood is fiberglass replace it with an all metal factory available lawn mower hood.
- 12- Any lawn mower tire wheel combo allowed. No bead protectors, tire chains or dual wheels.
- 13- Aftermarket header, gas pedal, shifter are permitted. Please make sure the shifter is mounted in a safe place so it can't be hit.
- 14- A small back plate is permitted but must be within the inside of fenders. Don't go overboard.
- 15- No hitting the rear of the lawn mower. If caught hitting in the back of the mower you will be warned once then will be out. This is considered a driver's door.

- 16- NO DRAMA. Don't show up trying to hurt someone or fight.
- 17-Roll-over driver is out of heat. If the driver's hand, foot or any body part touches the ground you will be out .
- 18- NO BATTERIES. You may use a battery to jump mower but must be removed before entering track.
- 19- Please put your number on both sides of the mower visible for officials to read and track winners.
- 20- We will go over all ground rules in a mowers drivers meeting before the heat.
- 21- if your helmet comes off you're out.
- 22- All mowers are recommended to have a roll over hoop that goes up and over the driver. Must be mounted behind the driver and be 5 inches above the driver's helmet. This is for your protection on the fast paced track.
- 23- If you have any questions please message within hours of 8am to 8pm