

# 2026 Farm Truck-ish

## Twisted Metal Motorsports

Any questions must be approved by the head inspector  
( ) either call or text 8am-8pm only.

**You must pass inspection within 2 times through inspection or you will not be permitted to run.**

**After your Truck has been inspected or flagged there will be no refunds.  
We are not responsible for any accidents or injuries!**

**You are only permitted to have 2 fires in your Truck. The second fire you're out.. This will result in a disqualification.**

**If your helmet comes off you're out.**

**THIS IS NOT A SET OF RULES BUT A SET OF GUIDELINES OF HOW TO BUILD YOUR TRUCK. IF IT DOESN'T SAY YOU SPECIFICALLY CAN DO SOMETHING THEN YOU CAN'T!**

### **Truck Preparation:**

NO PAINTING OR UNDERCOATING OF THE FRAME. NO BUFFING OR GRIDING FRAMES OR BODIES EXCEPT WHERE WELDING IS SPECIFICALLY ALLOWED IN THESE RULES. NO PAINTING IN THE INSIDE OF THE BODY OR TRUCK. IF THIS IS DONE THE TRUCK WILL NOT BE INSPECTED.

### **Fresh Trucks Only for Twisted Redemption**

#### **Truck General Rules**

1. 1/2 & 3/4 Ton Trucks Only
2. 2WD and 4WD trucks and Suburban's are allowed. 4WD vehicles must remove the front driveshaft. All frames must be pickup truck frames!
3. All cabs must match the frame (Year & Make) they are going on. no altering, no exceptions!
4. Maximum frame height is 26 inches, minimum frame height is 19 inches.
5. No body or suspension lifts allowed. No flat beds, or any other style frames!
6. Remove all glass, chrome, plastic, moldings, headliner, flammable material, A/C coolant, antifreeze, trailer hitches and interior decorating.
7. The stock gas tank must be removed. A small metal tank must be mounted in the rear seat area. The tank must be very secure and covered. Use proper rated fuel lines.

8. Plastic tanks must be in a metal box, no exceptions!! Electric fuel pumps are allowed.
9. Floor shifters are allowed. Ignition and wiring modifications (hotwire) are allowed.
10. You MUST run a roof sign.
10. Hood must have a 12" x 12" minimum hole to easily extinguish fires. Extra hole(s) in the hood are not required if header holes are at least 12" x 12".

### **BUMPERS/ FRAME**

1. Bumpers may be loaded. May use an Aftermarket replica bumper or a bumper approved by TMM. NO CHRYSLER POINTY OR POINTY REPLICAS. Do not abuse this rule.
2. You may hard nose your bumper right to the frame, don't cut the frame off any further back than the front side of the core support mount.
3. You may use (2) 10 Inch 2x2 square tube mounted on frame, 1 per side. You may also use (2) 4"x10" 3/8" bumper straps on one side of the frame only. 1 per frame rail, 2 straps total. Square tubing and bumper straps must touch the bumper and may not exceed 10" from your bumper. Can only weld 10 inches back from bumper to frame. This covers shocks / bumper straps. May cap the frame to mount your bumper. This is the only welding allowed on the frame.
4. **\*\*NO WELDING or Bolting Further than 10" FROM BACK OF BUMPERS FRONT OR REAR\*\*** If you have questions about this, please call.

### **Suspension**

1. Maximum frame height is 26 inches to the top, minimum frame height is 19 inches to bottom. No exceptions!
2. Stock Leaf spring pack that came with the truck only, no homemade springs!
3. You may clamp springs together with factory or homemade clamps, (6) per side. Homemade clamp size cannot exceed 3" wide material and cannot be thicker than 3/8". 7/16" bolts max is allowed to bolt the homemade spring clamps together.
4. Shackles and leaf spring perches must not be rewelded.
5. No leaf conversions, if your truck did not come with leafs and you want leafs pick a different truck.
6. A 2x2" 1/4 thick tube straight from axle to bottom of the frame is allowed to get height. Must be vertical.

### **Steering**

1. No welding or bracing tie-rods, must be a stock tie rod from a 1/2-ton truck. Aftermarket steering columns are allowed. NO HYDRAULIC RAM STEERING

### **Rear-End**

1. Any rear end allowed. If your rear end has a brace it must be 5" away from the frame.
2. 1 additional 3/8" chain per side is allowed to hold the rear end in place.

### **Cage**

1. You are allowed a driver's door plate/protection. This cannot exceed past 3" of the driver's door seam either way.
2. All cage components cannot exceed 6" OD and cannot be any smaller than 2" OD. The driver side door bar is the only bar you may stack metal, this can be up to 12" high but still must remain 4" of the floor.
3. The four-point cage must remain completely inside the cab. The total cage can not exceed 62" long.
4. You are allowed a dash bar, a bar behind the seat, and you can connect these 2 bars along the inside of the doors.
5. All cage components must be free floating, with 2 down legs to cab tin only! Down bars cannot be anywhere near the frame. Down bars must remain vertical. All cage material must remain 4" from the floor except down bars.
6. Dash bars must be 6" away from the transmission tunnel and any part of the drive train.
7. Rollover bar consists of (2) uprights and (1) horizontal bar over the cab. The 2 uprights may go to the frame with 2 down bars(kickers) to the body up to 24" behind the cab. This must not be attached or connected to the body. Suburbans will be allowed a 24" by 24" gas tank protector to mount the gas tank to. Must be mounted off the back seat bar and not go back past the back doors.
8. The cab can be welded to the box on the exterior only using 3" wide 1/8" strapping (cannot incorporate cage. CAN ALSO BOLT CAB TO THE BED IN (4) SPOTS USING (4) 3/4 BOLTS AND (8) 1/4 PLATES FOR WASHERS.
9. For safety all trucks must have (2) 2"x2" pieces of square tubing from the halo bar to the top side of the dash bar and no portion may extend past the dash bar.

### **Tires**

Tires no bigger than 16 inches. No split rims. No studded tires. Foam fill tires are not allowed at arena events. Double tires are ok. Valve stem protectors are ok. Tires may be screwed to rims. Wheel reinforcement is allowed if the reinforcement stays within the factory bead. Bead locks are allowed. They must not go past the rubber on the inside of the tire and the outside must remain inside the factory lip of the rim. Soil tires are allowed.

### **Body**

1. No creasing or shaping is allowed.

### **Body Bolts & Bed (box)**

1. Body bolts can be replaced, up to 3/4" max rod. You may add (4) additional body bolts in the box, and 4 additional body bolts in the cab. These can be welded to the frame but must be vertical and cannot exceed the 3/4" rod! 6"x 6" washers in stock mount locations are allowed. These bolts need to be straight up and down.
2. All body mount washers must be free floating.
3. No bolts may be run through the frame to create pins.
4. Body bolts can not be attached to anything other than body and frame.
5. The box must remain upright and in stock location, no tucking, shortening, or other manipulation to the box is allowed!

6. You are allowed a plate for your gas tank to sit on, the plate can be 3" wider in all directions of your fuel cell. It must be free floating if welded to the cage and can be bolted to sheet metal only if not connecting it to the cage you can connect it to your back-seat bar or cab or roll bar.

### **Tailgate**

1. The tailgate must remain upright in the stock location. Tailgate may be dropped a maximum of 8" but must remain vertical. You may weld the tailgate to the frame or bumper.
2. No tucking of the tail gate is allowed.
3. You have (3) ways of fastening your tailgate. You may weld a 3" wide strap per seam, or Chain/9 Wire at (2) locations per seam. Outside only.

### **Doors**

1. Doors may be welded 5" on 5" off with nothing larger than 3" wide by 1/4" thick strapping. If you choose not to weld, you are allowed to chain or 9 wire your doors shut.

### **Hood**

1. (6) locations of bolts, 3/8" chains or 9 wire will be allowed, 1" max. (2) may go to frame, the other (4) locations must be sheet metal to sheet metal. If you choose to use threaded rod it must be welded vertically within 4" of the stock core support location, 1" max. Only one of these three may be used. No sleeving of all thread.
2. No adding any metal to core support.

### **Batteries and Fuel Tank**

1. The fuel cell is highly recommended to be in a steel box. This is to be located in the most forward center of the box or inside of the cab. Gas line to be run in a protective conduit.
2. Two batteries max, batteries must be covered or in a box. All battery boxes and fuel cells must be securely fastened.
3. Do not weld battery boxes, tranny coolers, and pedals to the cage.

### **Drive Train**

#### **Engine**

1. Motors may interchange, but it must be within 4" of the factory location.
2. No distributor protectors & transmission braces
3. You are allowed a front lower cradle with pulley protector. The cradle must attach to a factory style engine mount; this is the only way to tie the engine down. No part of the lower cradle can extend any further back than the middle of the block.
4. Carb halos are allowed, nothing can extend past the last spark plug hole on the block.
5. No pan protectors, side bars, etc. can go back towards the transmission to tie it in.
6. Header protectors are allowed; this can be accomplished with a piece of 4"x4" x1/4" welded around header or to carb halo only
7. If your truck does not have an engine crossmember you will be allowed to weld an 8"x8"x8" box to the side of your frame rails for your motor to mount to. This is for motor mounting purposes only.

### **Transmission**

1. No transmission braces whatsoever or aftermarket cases.
2. An aluminum bell or steel bell as well as aftermarket tail housings are allowed but may only be secured by the pump bolts. All sheet metal must be at least a 1/2" from the bell.
3. You may have a transmission cooler but cannot strengthen the truck in any way and must be secured.
4. Any driveshaft allowed, including sliders.

### **Radiators**

1. Must be in stock location.
2. Aftermarket stock radiators allowed.
3. Radiator protectors /guards are allowed must be flat 1/8" and can be bolted using (10) 3/8" bolts total (not welded) or You may bolt OEM FULL SIZE TRUCK air conditioner condenser in front of the radiator using (6) 3/8" bolts and standard washers. Pick one only one.
4. No homemade radiators.
5. If you do not have a place to set your radiator you may weld a 3"x3" x 1/4" thick angle iron from frame rail to frame rail to set radiator on, this must be in stock location.

Once the truck is through inspection it may not leave the premises. If point blank cheating you will be loaded. One entry per truck.

Any questions please contact Twisted Metal Motorsports