

2026 STOCK MOWER RULES

General Rules

1. • Mowers must remain belt-driven.
2. • John Deere 200 Series tractors are allowed
3. • Maximum engine size is 22 HP.
4. • Pre-ran mowers are permitted.
5. • No batteries permitted.
6. Fuel System
7. • A working fuel shut-off valve is required where we can get to it with the hood shut.
8. Engine & Exhaust
9. • Spark plug protectors are allowed but may not touch, reinforce, or strengthen the frame in any way.
10. • Headers or exhaust stacks are allowed but may not touch, reinforce, or strengthen the frame in any way.
11. • A pull-string throttle or gas pedal may be used to operate the governor.
12. • No pulley swaps allowed.
13. Tires & Wheels
14. • Any tire and wheel combination is permitted.
15. • Tire chains and dual wheels are not allowed.
16. Hood & Front End
17. • A maximum of two (2) pieces of 5/8" all-thread may be used to secure the front of the hood.
18. • An all-metal hood may be installed.
19. • Sheet metal may be added to the front portion of the existing hood.
20. • Factory mower bumpers may be used but must be bolted on with no more than two (2) bolts per side.
21. Frame & Reinforcement
22. • No modifications may strengthen the frame unless specifically stated in these rules.
23. • A maximum of two (2) reinforcement plates measuring 3" x 3" x 1/8" may be used on pre-ran mowers.
24. Leg Bars & Fenders
25. • Leg bars may not extend higher than the top of the rear fenders.
26. • Leg bars may extend only to the centerline of the rear tires.
27. • Leg bars may not attach to or strengthen the frame in any way.
28. • Rear fenders may be lowered.
29. Steering
30. • All steering components must remain factory.
31. • No steering reinforcement is permitted.