

SPECIFICATIONS (EN590 10ppm):

Test	Units	Limits	Method
Density at 15°C *	kg/m ³	820.0 - 860.0	ASTM D4052
ASTM Color *		2.0 Max.	ASTM D6045
Flash Point P.M.C.C*	°c	60 Min.	ASTM D93A
Total Sulphur	mg/kg	10 Max	ASTM D2622
Copper Corrosion, 3hrs at 100°C		1.0 Max.	ASTM D130
Kinematic Viscositv at 40°C	cSt	2.0-45	ASTM D445
Pour Point *	°c	+6 Max.	ASTM D5950
Ash Content	wt%	0.01 Max	ASTM D482
Water Content	mg/kg	200 Max.	ASTM D6304
Sediments by Centrifuge	vol%	0.01 Max	ASTM D2709
Derived Cetane Number		51 Min.	ASTM D6890
Cetane Index		46 Min.	ASTM D4737A
FAME Content	vol%	7.0 Max.	EN 14078
Lubricity (HFRR)(WSD) @ 60°C		460 Max	EN 121561
Distillation			
50 % Recovery	°c	Report	ASTM D86
90 % Recovery	°c	Report	
95 % Recovervy	°c	360 Max.	
F.B.P	°c	Report	

