

Compare Products

| | |
|--------------|--------------|
| Code | 71382 |
| Model | XK |



| | |
|-------------|---|
| Note | <p>ERON D-1 DASHBOARD Connect Calypso Connect (Motor, Battery, ERON D-1) Dual Speed trigger Fiber Carbon Proplock Propeller Battery Gauge Bypass System HD Shaft Seal Carry Handle Cleaning and Lubrication Kit Tow Leash with boltsnap and bungee Extra Bolt snap</p> <p>- Top speed is delivered with fully charged battery - Diver : 70kg weight, 170cm high - drysuit - double 12 tanks - horizontal trim - Conditions : sea water - no flow/current</p> |
|-------------|---|

Dimensions

| | |
|-------------------------------|------------------------------------|
| Use | TECH / COMMERCIALLONG RANGE / CAVE |
| Length | mm 975 (inch 38,4) |
| Width | mm 462 (inch 18,2) |
| Height | mm 364 (inch 14,33) |
| Body diameter | mm 197 (inch 7,8) |
| Weight without battery | kg 17 (lb 37,48) |
| Weight with battery | kg 25 (lb 55,12) |
| Material type | Aluminum Body |

Performance

| | |
|-----------------------------------|---------------------------|
| Max static thrust | N 375 (lb 84,3) |
| Top speed | mt/min 100 (ft/min 328) |
| Run time at max speed/drag | min 100 |
| Run time at cruise speed | min 330 |
| Maximum operational depth | mt 200 (ft 656) |
| Test depth | mt 300 (ft 984) |
| Buoyancy/ trim | Neutral Trim and Buoyancy |

In-water usage temperature

°C -5/+35 (°F +23/+95)

Runtime-range

| SPEED | BURNTIME | RANGE |
|------------------|----------|-------------------|
| FULL TRIGGER | 100 MIN | 8,1 (4,4) KM (nm) |
| 80 MT/MIN | 120 MIN | 9,6 (5,2) KM (nm) |
| 60 MT/MIN | 200 MIN | 12,0(6,5) KM (nm) |
| CRUISE 45 MT/MIN | 330 MIN | 14,8(8,0) KM (nm) |

- Top speed is delivered with fully charged battery
- Diver : 70kg weight, 170cm high - drysuit - double 12 tanks - horizontal trim
- Conditions : sea water - no flow/current

Battery type

| | |
|--------------------------------|-------------------|
| Battery type | LI-ion |
| Nominal Voltage | Volt 36 |
| Nominal Capacity | Wh 1340 |
| Maximum recharging time | h 8 |
| Charger power supply | 90/240 - 50/60 Hz |

Features

| | |
|--------------------------------------|---|
| Smartphone connect | ● |
| External Charge | |
| Battery Gauge | ● |
| Li-ion Battery | ● |
| Fastening device | ● |
| Main Switch | ● |
| Proplock Propeller | ● |
| Speed Adjustment | ● |
| By-pass System | ● |
| Easy Trim | ● |
| Easy Inspect | ● |
| New Handle Design | ● |
| Sealed Motor Compartment | ● |
| NBS - Neutral Buoyancy System | ● |
| Made Salt Resistant | ● |
| Motor Protection | ● |
| Battery Protection | ● |
| Certifications | ● |

Features legend:

● : standard

○ : optional

 : not available