



- STEK DMM 27 is a Multifunctional multimeter with high precision and high performance can measure AC/DC voltage, current, resistance, capacitance, frequency, duty ratio, temperature and True RMS.
- It has a big Bargraph LCD Display with Double color backlight to warn the users about high voltage danger indication.
- It also featured with input jack indicate LED to avoid wrong input and any damage caused.
- It also can test NCV(non-contact voltage), live line, diode , continuity etc. With a bracket on the back, convenient to place it on the table and read the values

Multimeter's Features:

- Can measure AC/DC voltage, current, resistance, capacitance, frequency, duty ratio.
- Also can test NCV(non-contact voltage), live line, diode,temperature and continuity.
- specially designed with temperature measurement function.
- Data hold function, seperate display backlight and work light.
- Big LCD display with double color backlight and Bargraph is more convenient to use.
- 2AA batteries and Auto power off.



STEK DMM 27 TECHNICAL SPECIFICATIONS

Function	Range	Accuracy
		STEK DMM 27
DC Voltage	600mV/6V/60V/600V/1000V	±(0.5%+3)
AC Voltage	600mV	±(1.0%+5)
	6V/60V/600V/750V	±(1.0%+5)
DC Current	600uA/6000uA/60mA/600mA	±(0.8%+3)
	10A	±(1.2%+3)
AC Current	600uA/6000uA/60mA/600mA	±(1.0%+3)
	10A	±(1.5%+3)
Resistance	600Ω/6kΩ/60kΩ/600kΩ/6MΩ/60MΩ	±(0.8%+3)
Capacitance	10nF/100nF/1μF/10μF/100μF/1mF/10mF	±(4.0%+3)
	100mF	±(5.0%+5)
Frequency	10Hz/100Hz/1kHz/10kHz/100kHz/1MHz/10MHz	±(1.0%+3)
Duty	1%~99%	±(1.0%+2)
Temperature (°C/°F)	-40°C~1000°C	±(1.0%+3)
	-40°F~1832°F	±(1.0%+3)
Counts		6000 Counts
Auto/Manual range		Auto
Display		LCD dual display
Bargraph		√
Live test		√(sound and light alarm)
NCV		√(sound and light alarm)
Diode test		√
Continuity		√(sound and light alarm)
Max/Min hold		√
data hold		√
True RMS		√
bandwidth		1kHz
Battery test (1.5V/9V)		
Low battery indication		√
Auto power off		√
Double color backlight		√
Input jack LED indicate		√
Work light		√
Power		2xAA batteries
Safety Rating	EN61010-1,-2-030 EN61010-2-033, EN61326-1 CAT III 1000V,CATIV 600V	
Accessories	Rexine Carrying Case, CATIII 1000V, CATIV 600 V Test Leads, K Type Thermocouple, 2 numbers AA Batteries	