

Clamp Earth Testers

CET09 / CET 27 / CET 36



Clamp Earth Testers

CET09 / CET 27 / CET 36



Model	CET 09	CET27	CET36
Resistance Range	0.010Ω ~ 1200Ω	0.010Ω ~ 200Ω	0.010Ω ~ 1200Ω
Current Range	-	-	0.00mA ~ 20.0A
Resistance Measurement Accuracy	Range	Resolution	Accuracy
	0.010Ω-0.099Ω	0.001Ω	±(1%rdg+0.01Ω)
	0.10Ω-0.99Ω	0.01Ω	±(1%rdg+0.01Ω)
	1.0Ω-49.9Ω	0.1Ω	±(1%rdg+0.1Ω)
	50.0Ω-99.5Ω	0.5Ω	±(1.5%rdg+0.5Ω)
	100Ω-199Ω	1Ω	±(2%rdg+1Ω)
	200Ω-395Ω	5Ω	±(5%rdg+5Ω)
	400-590Ω	10Ω	±(10%rdg+10Ω)
	600Ω-880Ω	20Ω	±(20%rdg+20Ω)
900Ω-1200Ω	30Ω	±(25%rdg+30Ω)	
Current Measurement Accuracy	0.00mA -9.95mA	0.05mA	±(2.5%rdg+1mA)
	10.0mA -99.0mA	0.1mA	±(2.5%rdg+5mA)
	100mA -300mA	1mA	±(2.5%rdg+10mA)
	0.30A-2.99A	0.01A	±(2.5%rdg+0.1A)
	3.0A-9.9A	0.1 A	±(2.5%rdg+0.3A)
	10.0A-30.0A	0.1 A	±(2.5%rdg+0.5A)
Clamp Size	65mm×32mm		
Tester Size	285mm×85mm×56mm		
Tester Weight	1160g		
Power Supply	6VDC (4 PCS of No.5 Alkaline dry batteries)		
Single Measurement Time	0.5 second		
LCD Screen	4 Digits LCD display, 47mm x 28 mm		
Data Memory	99 groups		
Audible And Visible Alarm	"du—du—du" for alarming , press AL to turn on/off		
Alarm Threshold Setting Range	Resistance:1-199Ω ; current :1 - 499mA (only C type)		
Jaw Opening Size	32mm		
Protection Class	Double insulation		
Shift	Automatically		
RS232 Interface	Optional		
Accessories	Tester: 1PCS; Test Ring: 1PCS; Instrument Case: 1PCS		