

4" RECESSED HOUSING

New Construction

- Housing
- Die-formed aluminum for maximum heat dissipation and rust protection
- Housing adjusts to 1/2" to 1 3/8" ceiling thickness. Trims are held in place with high tension clips
- •Housing is compatible with IC and Non-IC applications.



Connection

E26 Standard Edison Base Socket.

Thermal Protector

Standard thermal protection device guards against improper installation and misuse of insulation material.

Junction Box

UL listed for through branch wiring.

1/2" and 3/4" romex wiring knockouts and four romex knockouts with integral strain clamps, all

knockouts have true pry-out slots.

J-Box is designed for straight through conduit runs. Fixture fully assembled including pre-wired ballast for easy installation.

Removable access plates for easy installation.



Air-Shut

Provided with gasket to prevent airflow from heated or airconditioned spaces. Meets or exceeds all national air flow requirements.

Listing & Warranty

UL listed to US and Canada standards for wet locations. 5-year limited warranty.



LED RECESSED HOUSING

New Construction

Product Ordering code













340 Marshall Avenue #103, Aurora IL 60506 | Telephone 630.486.1070 | Fax 630.486.1034 Email: info@fudakinlighting.com | www.fudakinlighting.com

Housing Type	Installation Type	Internal Series Number	SIZE
RC - RECEESSED CAN	NC - NEW CONSTRUCTION RM - REMODEL CAN	F1~FN	04 - 4inch


Outline Drawing & Overall Size





TRIMS







Third SWH1 Was was at long Listed Softin Glass Shower Trim 30W Max. RAR20/R20 O. D. 5"



FDK-GT-F1-04-WH
White Gimbal
50W Max.
RAR20
O. D. 5"



FDK-SGT-F1-04-WH 4" Square Gimbal Trim White PRR20/R20

Important notes:











340 Marshall Avenue #103, Aurora IL 60506 | Telephone 630.486.1070 | Fax 630.486.1034 Email: info@fudakinlighting.com | www.fudakinlighting.com