

DOWN LIGHTS

Square Downlight External Driver



Ordering Information

Model No.	Item name	Lumens ² (lm)	Watts (w)	CCT ¹ (k)	Efficacy (lm/w)	CRI	Lifetime ³ (h)	Beam Angle	Base type	Dimmable	Voltage (v)	Certification
FDK-SDL-EX-F1-12-04-13W-XXK-D	Slim Downlight External Driver 13W	750	13	2700K 3000K	58	90	35000	/	/	YES	120	Pending
FDK-SDL-EX-F1-12-06-16W-XXK-D	Slim Downlight External Driver 16W	1100	16	3500K 4000K	69	90	35000	/	/	YES	120	Pending
FDK-SDL-EX-F1-12-08-20W-XXK-D	Slim Downlight External Driver 20W	1500	20	5000K	75	90	35000	/	/	YES	120	Pending

1. CCT Range complies to ANSI C78.377-2008.

2. Rated life is based on 70% lumen maintenance, and engineering testing and probability analysis.

Dimensions

Model	MOL	Diameter
FDK-SDL-EX-F1-12-04-13W-XXK-D	0.93"	4.92"
FDK-SDL-EX-F1-12-06-16W-XXK-D	0.93"	6.69"
FDK-SDL-EX-F1-12-08-20W-XXK-D	0.93"	8.86"

