

Square Downlight

4", 6", 8" Square Downlight - Smooth



DESCRIPTION

The Square Downlight - Smooth is compatible with most recessed standard housings. Ideal for both remodel or new construction applications. The retrofit kit comes with a disconnect screw-in base lead for easy installation into standard incandescent sockets.

PRODUCT SPECIFICATIONS

- White painted Diecast body is appropriate for heat dissipation.
- 3 Tension Clips pre-installed on unit for easy installation.
- E26 medium screw-base Edison connector provides easy retrofit of incandescent housings.
(GU10 and GU24 socket adaptor available - sold separately)

LED LIGHT ENGINE

- Protected LED driver performs at 120V (120-277V available).
- Dimming down to 10% with most dimmers (at 120V only).
- CCT 2700K, 3000K, 4000K, 5000K available
- CRI ≥80 or ≥90
- Long life LED chips guaranteed up to 50,000hours.

WARRANTY

Guaranteed five years from the purchase date of the product, against mechanical defects in manufacturing.

LISTINGS


- cULus classified
- Energy star qualified
- Wet locations (Not suitable for coastal/salt water area)
- Damp locations
- RoHS compliances
- Tested in accordance with IESNA LM79 & LM80

PERFORMANCE DATA

	3000K
Input Voltage	120V
Input Power	11W, 16W
Frequency	50 / 60Hz
Operation temp	-30 °C ~ 40 °C (-22°F ~ 104°F)
Lumens	680, 1140, 1210
CRI	≥ 90



SPECIFICATIONS / DIMENSIONS



PRODUCT CODES

Catalog Number		COLOR TEMP		CRI	
Model	Description				
	4" LED Retrofit / Square Smooth / White	-27	2700K	-xx80	CRI ≥80
FDK-SDLS-F1-12-04-11W-XXX-D-Y	4" LED Retrofit / Square Smooth / Black	-30	3000K	-xx90	CRI ≥90
	4" LED Retrofit / Square Smooth / Satin Nickel	-40	4000K		
	4" LED Retrofit / Square Smooth / Bronze	-50	5000K		

Catalog Number		COLOR TEMP		CRI	
Model	Description				
	6" LED Retrofit / Square Smooth / White	-27	2700K	-xx80	CRI ≥80
FDK-SDLS-F1-12-06-16W-XXX-D-Y	6" LED Retrofit / Square Smooth / Black	-30	3000K	-xx90	CRI ≥90
	6" LED Retrofit / Square Smooth / Satin Nickel	-40	4000K		
	6" LED Retrofit / Square Smooth / Bronze	-50	5000K		

Catalog Number		COLOR TEMP		CRI	
Model	Description				
	8" LED Retrofit / Square Smooth / White	-27	2700K	-xx80	CRI ≥80
FDK-SDLS-F1-12-08-16W-XXX-D-Y	8" LED Retrofit / Square Smooth / Black	-30	3000K	-xx90	CRI ≥90
	8" LED Retrofit / Square Smooth / Satin Nickel	-40	4000K		
	8" LED Retrofit / Square Smooth / Bronze	-50	5000K		