

RF Directional Coupler



AWJ0701-C143106




75Ω 7.0dB Directional Coupler

5-1225MHz


Outline Drawing(mm)



Electrical structure



Recommended layout(mm)




Pin Connections

Input	1
Coupling	3
Output	5
Ground	2
External 75 Ω	4

Features

- Operating temperature range:-40°C to +85°C
- Storage temperature range: -55°C to +100°C
- 260°C Reflow Compatible
- RoHS compliant and lead free
- Input Power:2W MAX
- DC Current:500 mA MAX









Applications

- For Docsis 3.0&4.0Cable Modem.
- For Wideband Push-pull Amplifiers.
- For CATV Amplifiers Module & Set top box.
- For CATV Optical Receivers and Amplifiers.

Electrical Specifications:TA=25°C, 0dBm, Z0=75Ω

Parameter	Test Conditions	Units	Min	Typ	Max
Coupling(Pin1-3)	5-1225MHz	dB	7.0	7.5	8.0
Main line Loss(Pin1-5)	5-700MHz	dB	—	1.8	2.0
	700-1225MHz	dB	—	2.0	2.2
Input Return Loss(Pin1)	5-700MHz	dB	15.0	17.0	—
	700-1225MHz	dB	15.0	16.0	—
Output Return Loss(Pin5)	5-700MHz	dB	18.0	26.0	—
	700-1225MHz	dB	18.0	20.0	—
Coupling Return Loss(Pin3)	5-700MHz	dB	15.0	18.0	—
	700-1225MHz	dB	15.0	16.0	—
Isolation(Pin3-5)	5-100MHz	dB	28.0	35.0	—
	100-700MHz	dB	40.0	42.0	—
	700-1225MHz	dB	26.0	29.0	—




RF Directional Coupler AWJ0701-C143106




Recommended Soldering Temperature Graph:


Typical RoHS Reflow Profile






Packaging Dimension For Carrier Tape(UNIT:mm):



QUANTITY
1500PCS/Reel
18000PCS/ Big Carton



SPEC	8	12	16	24
DIM A±0.1	8.5	12.5	16.5	24.5
DIM B±0.1	2.3	2.3	2.3	2.3
DIM C±0.1	100	100	100	100



Length of the preceding blank space: 300MM Min
Length of the trailing space: 300MM Min

The label should be stuck on the side without positioning holes.



Advanced Wire Coil Technology LLC

Web: www.awcoil.com E-mail: Sales@awcoil.com Phone: (321)-321-6168 Florida,USA