

XTREME POWER CONVERSION J40 & J40E

Ultra-Slim Surge PDU // 120VAC or 208/230VAC

For more information, visit www.xpcc.com/j40



Compact Surge Protection & Quick Power Reset – J40 Surge PDU

The Xtreme Power J40 delivers advanced surge suppression in an ultra-slim profile—ideal for mounting behind today's thin digital displays. With simple wall installation, side-access receptacles, and an illuminated reset button for instant visual status and power restoration, the J40 provides clean, protected power to signage in hotels, restaurants, healthcare facilities, airports, and campuses.

Beyond digital displays, the J40 is also ideal for kiosks, gaming machines, point-of-sale equipment, and small electronics that require uninterrupted performance and convenient power reset access.

For a slim form factor UPS, reference the J60 ups at www.xpcc.com/j60

PRODUCT SNAPSHOT

- › Available Models (Local Reset): J40 (120V), J40i (230V)
- › Available Model (Remote Reset): J40E (120V) with 10 ft remote power reset cable
- › Ultra-slim, lightweight design easily mounts behind flat-panel displays
- › Primary Applications: digital signage, kiosks, AV devices, gaming machines, point-of-sale (POS)
- › Warranty: 5-year standard (USA & Canada)

FEATURES

Advanced Surge Protection

– Absorbs up to 2400 Joules to safeguard connected electronics from spikes, surges, and transients

Illuminated Power Reset

Button – Provides clear visual status and allows users to quickly restore power without unplugging equipment; J40E model includes remote-mounted illuminated reset on a 10 ft cable

Slim, Wall-Mount Design

– Side-facing inlet and receptacles enable flat installation behind ultra-thin displays

Thermal Fuse MOV Modules

– Built-in protection against overvoltage and heat, UL 1449 3rd Edition compliant

Flexible Mounting – Brackets included for wall or ceiling mounting in any orientation

Optional Detachable Input Cord

– Right-angle, offset plug allows tight-space installations behind screens and enclosures

MODEL SELECTION GUIDE

MODEL NUMBER		J40	J40E	J40i
INPUT	Capacity		10A	
	Voltage	120VAC		208/230V
	Frequency		50/60Hz	
OUTPUT	Voltage	120VAC		208/230V
	Frequency	50/60Hz		
	Power reset button	Mounted on Unit Side	On 10 ft Cable for remote mounting	Mounted on Unit Side
POWER RESET	Surge suppression		2400 joules	
	Button	Unit Side Mounted	Remote mount with 10 ft cable	Unit Side Mounted
PHYSICAL	Status		Illuminated	
	Dimensions (W x D x H)	8.07 x 3.35 x 1.22 in		8.07 x 3.35 x 1.22 in
	Weight	2.0 lbs		2.0 lbs
	Line cord		IEC C14 inlet	
ENVIRONMENT	Receptacles	(3) 5-15R		(3) IEC C13
	Temperature	-4–158°F (-20–70°C)		
	Humidity	0–90%		
WARRANTY	Altitude	11,500 ft above sea level		
			5 year warranty (USA & Canada)*	

*Warranty outside of USA & Canada is 3 years.



Mounting brackets

Power Reset Button

(3) 5-15R receptacles



XTREME
Power Conversion®

Protect your business.

XPC USA / Denver, CO / sales@xpcc.com

www.xpcc.com

©2025 Xtreme Power Conversion Corporation. All Rights Reserved. J40.03U (Rev 10/15/25)