

Project Name: \_\_\_\_\_  
 Date: \_\_\_\_\_ Note: \_\_\_\_\_

## LED Wraparound - LW102 Series



**Application:** Commercial; Industrial; Warehouse; Retails; Residential garage; school/institution; supermarket....



Specifications		
Model No.	LW-4FT-40W-CCT	LW-8FT-80W-CCT
Power:	40W	80W
Input Voltage:	AC110-277V	
Luminous Flux:	5,200	10,400
Efficacy:	130 lm/W	
Power Factor:	>0.9	
THD:	<10%	
CCT:	3000K-4000K-5000K Adjustable	
CRI:	>80	
Working Life:	>50,000 hours	
Working Temperature:	-10°F to 105°F	
DLC Listing	S-4FIDSR	S-YNM289
Product Size:	46.85"x6.89"x2.76"	93.70"x6.89"x2.76"
Qty/Master Pack	5	3
Master Pack Size:	48.7"x13.6"x25.5"	94.9"x11.0"x9.3"
Master Pack Weight	38.58 lbs	46.74 lbs

### FEATURE

- Acrylic lens available in 4 FT and 8FT length
- High energy efficiency: 32W replace 2x32W T8
- Suitable for damp location
- Steel housing
- Equipped with heat resistant prismatic lens
- 0-10V Dimmable
- Chain or surface mount installation
- Option: available with emergency backup kit/ motion sensor

### OPTION

- Emergency Driver
- Motion Sensor

## ORDERING CODE DEFINITION


**EXAMPLE: HY-4FT-LW102-40W-3CCT**

Company Code	Length	Product	Wattage	CCT
	4FT	LW: LED Wraparound	40W: 4FT 40W	CCT: 3000K-4000K-5000K
	8FT		80W: 8FT 80W	


## LED Wraparound - LW102 Series

### DIMENSION


8ft Front View




Side View



4ft Front View




Side View




### PHOTOMETRIC REPORT

LUMINOUS INTENSITY DISTRIBUTION DIAGRAM



C0 PLANE ISOLUX DIAGRAM (UNIT: lx)



## LED Wraparound - LW102 Series

### INSTALLATION

