



SeaBlaze Typhoon

LED Through-Hull Underwater Light

Brighter, more advanced, more features. The evolution continues as Lumitec answers the call of our customers and introduces the Typhoon Through-Hull Underwater Light. Typhoon sets a new standard for performance, reliability, and value in through-hull underwater lights. Typhoon delivers more than 10,000 measured lumens (white), and a modular quick-change design for easy in-water service and upgrades. Our innovative internal relay simplifies wiring and significantly reduces installation costs and complexity. Solid bronze housing requires a 3" mounting hole (3.635 flush mount). Full-color control using any standard on/off switch. Or use Lumitec's "Poco" Digital Lighting Control, sold separately, for even more advanced features.

Specifications:

Lumens:	10,000+
CCT:	6500K
CRI:	70+
Voltage:	10-30vDC
Rated Watts:	120W
IP Rating	IP68
Housing	Bronze

Key Features:

- Available in full-color spectrum with color cycle mode or dual-color white/blue with cross fade modes.
- Completely water sealed and IP68 compliant.
- Easy Installation – small 3" through-hull hole and simple 3-wire hook up.
- PLI enabled - Poco Digital Lighting Control compatible.
- Constructed of marine grade bronze and heat tempered glass.
- Available with transom mount or flush mount bezel options.
- Over 2,000+ hour of rigorous ASTM-B-117 Salt Spray Chamber testing.
- Proudly designed and manufactured in the USA.
- 3 Year warranty on all Lumitec products.

Product Details:

SKU	MOUNT	COLOR OUTPUT	CRI*	CCT*	VOLTAGE	12VDC	24VDC	LUMENS†
101448	Surface	Dual-Color White/Blue Cross Fade, Non-Dim	70+	6500	10-30vDC	10A	4.5A	10,000
101449	Surface	Spectrum RGBW	70+	6500	10-30vDC	10A	4.5A	10,000
101450	Flush	Dual-Color White/Blue Cross Fade, Non-Dim	70+	6500	10-30vDC	10A	4.5A	10,000
101451	Flush	Spectrum RGBW	70+	6500	10-30vDC	10A	4.5A	10,000

* Lumens, CRI & CCT applies only to white light.

† Integrating sphere measured lumens within 1 minute of initial startup

Features:



RGBW
Full-Color



10K
Lumen
Output



Color Cycle



TTP
Timed Toggle
Protocol



PLI
Power Line
Instruction



CM
Color Match
Commitment



3
Year
Warranty



Certifications:



IP Rated



European
Conformity




Beam Pattern: SeaBlaze Typhoon - LED Through-hull Underwater Light

SeaBlaze Typhoon - Flood Pattern

	Illuminance at a Distance		
	Center Beam fc	Beam Width	
4.3ft	174 fc	13.2 ft	13.9 ft
8.7ft	42.4 fc	26.6 ft	28.2 ft
13.0ft	19.0 fc	39.8 ft	42.2 ft
17.3ft	10.7 fc	53.0 ft	56.1 ft
21.7ft	6.81 fc	66.5 ft	70.4 ft
26.0ft	4.75 fc	79.6 ft	84.3 ft

■ Vert. Spread: 113.7°
■ Horiz. Spread: 116.7°

Illuminance at distance



Iso Candela Plot

Dimensions:

- Diameter: 4 in (10.16cm)
- Depth: 5.125 in (13.01cm)
- Mounting Hole: 3 in (1.18cm)

