



4503-55 Ave. NW Edmonton, T6B-3S8 AB, Canada

**Wellhead Drive CXD-22000-Dual (Direct Drive Dual 2x60HP or 2x75HP or 2x100 HP max.)**

**TECHNICAL SPECIFICATION**

<b>MODEL</b>	<b>CXD-22000-Dual (Direct-Drive)</b>
Max. Speed	500 RPM
Max. Power Rating	200 HP
Basic Dyn. Load Rating Ca.	1260 kN
Weight, Drive with Mount and Guard	1180 lbs
Gear Ratio (for Back-Spin-Control) □	5.3:1
Brake Torque	4210 Nm / 3105 ft-lbs
Continuous Torque	4068 Nm / 3000 ft-lbs
Well Connection, Standard	3 1/8"-3000
Well Connection, Alternative	4 1/16"-3000
Polished-Rod Size	1 1/4" or 1 1/2"
Stationary Sealing System	Special Rope Packing
Dynamic Sealing System (Seal-Housing)	Premium Sealing System comes with advanced arranged O-Rings, internal U-Cup Seals and special Buffer-Seals.
Oil Type	Gear-Oil 75W90
Oil Filling Capacity	37 Liter
Oil Change Interval	6 Month
Back-Spin-Control	Back-Spin-Control takes place due to a well-proven Oil-Flow retarding Brake-System. No significant Heat-Generation and no Sparks possible (unlike other manufacturers).

**CXD-22000 SERIES DUAL MOTOR 2x60 or 2x75hp or 2x100hp max. (200HP)**

