



4503-55 Ave. NW Edmonton, T6B-3S8 AB, Canada

## Wellhead Drive CXD-20000-H Series (HYDRAULIC DRIVE 75hp)

### TECHNICAL SPECIFICATION

<b>MODEL</b>	<b>CXD-20000-H (Hydraulic Drive)</b>
Max. Speed	500 RPM
Max. Power	75 HP
Hydraulic Motor	80 / 90 /112 /130 (SAE-D - 1-3/4" - Keyed)
Basic Dyn. Load Rating Ca.	720 kN
Brake Torque	Check Valve with Orifice
Continuous Torque	2305 Nm / 1700 ft-lbs
Weight, Drive with Mount and Guard	460 lbs
Gear Ratio	4:1
Well Connection, Standard	3 1/8"-3000
Well Connection, Alternative	4 1/16"-3000
Polished-Rod Size	1 1/4" or 1 1/2"
Stationary Sealing System	Special Rope Packing
Dynamic Sealing System (Seal-Housing)	Premium Sealing System comes with advanced arranged O-Rings, internal U-Cup Seals and special Buffer-Seals.
Oil Type	Gear-Oil 75W90
Oil Filling Capacity	5 1/2 Liter
Oil Change Interval	6 Month
Back-Spin-Control	Back-Spin-Control takes place due to an orifice in the checkvalve.

### CXD-20000-H 75HP

