



4503-55 Ave. NW Edmonton, T6B-3S8 AB, Canada

Wellhead Drive CXD-18000-G Series (75HP)

TECHNICAL SPECIFICATION

MODEL	CXD-18000-G (G-Drive)
Max. Speed	500 RPM
Max. Power Rating	Single Motor 75 HP
Basic Dyn. Load Rating Ca.	720 kN
Weight, Drive with Mount and Guard	860 lbs
Gear Ratio	3.1:1
Brake Torque	2470 Nm / 1822 ft-lbs
Continuous Torque	2305 Nm / 1700 ft-lbs
Well Connection, Standard	3 1/8"-3000
Well Connection, Alternative	4 1/16"-3000
Polished-Rod Size	1 1/4" or 1 1/2"
Stationary Sealing System	Special Rope Packing
Dynamic Sealing System (Seal-Housing)	Premium Sealing System comes with advanced arranged O-Rings, internal U-Cup Seals and special Buffer-Seals.
Oil Type	Gear-Oil 75W90
Oil Filling Capacity	27 Liter
Oil Change Interval	6 Month
Back-Spin-Control	Back-Spin-Control takes place due to a well-proven Oil-Flow retarding Brake-System. No significant Heat-Generation and no Sparks possible (unlike other manufacturers).

CXD-18000-G 75HP

