**SHARE** 

# Compact Track Loaders / T550 Compact Track Loader Specifications & Options

Standard	✓ Optional	N/A Not Applicable	Units	US

#### **Bobcat T550**

Configuration	Standard	Roller Suspension Option
∪ Eligilio		
Emissions Tier (EPA)	Tier 4	Tier 4
Engine Cooling	Liquid	
Engine Fuel	Diesel	
Horsepower	66 hp	
Turbocharged Engine	[	

#### $\bigcirc$ Performance

Rated Operating Capacity (SAE)	1,995 lb	1,895 lb
Operating Capacity (50% of Tip)	2850 lb	2707 lb
Tipping Load	5700 lb	5414 lb
Operating Weight	7557 lb	7758 lb
Travel Speed	7.1 mph	7.1 mph
Travel Speed (2-speed option)	10.4 mph	n/a
Ground Pressure (Rubber)	4.9 psi	5.8 psi

# ullet Capacities

Fuel Tank	36.5 gal	36.5 gal
-----------	----------	----------

## 

System Relief @ Quick Couplers	3,500 psi	
Auxiliary Std Flow	17.1 gal/min	
Auxiliary High Flow	26.7 gal/min	

#### $\odot$ Dimension

Length	133 in		
Length without Attachment	104.6 in		
Length with Standard Bucket	133 in		
Width	67 in 71.5 in		
Width (with bucket)	68 in	74 in	
Height	77.8	in	
Height with Operator Cab	77.8 in		
Height to Bucket Hinge Pin	114.5 in		
Reach @ Maximum Height	19.3 in		
Turning Radius	80 in	80 in	
Length of track on ground	54.1	in	
Track Width	12.6	in	
Track Width - Optional	15.8 in		

## $oldsymbol{ ilde{\ominus}}$ Features

Joystick Control	ightharpoons
Air Conditioning	✓
Backup Alarm	
BICS System (Interlock)	
Cab Heater	$\checkmark$
Operating Lights	
Suspension Seat	
Two Speed Travel	N/A
Deluxe Instrumentation	$\checkmark$
Engine Shutdown	
Hydraulic Bucket Positioning	$\checkmark$
High Flow Option	✓
Auxiliary Hydraulics	
Bob-Tach Attachment System	
Power Bob-Tach	
ACS (Switchable Controls)	✓
Ride Control	$\checkmark$
Horn	

Certain specification(s) are based on engineering calculations and are not actual measurements. Specification(s) are provided for comparison purposes only and are subject to change without notice. Specification(s) for your individual equipment will vary based on normal variations in design, manufacturing, operating conditions, and other factors.