

SAN LUIS OBISPO TAPROOM

Equipment Spec Sheet

- *Stage 12ft deep x 16ft wide with front additional catwalk at front 3ft deep x 10ft wide
- *Mixer- Beringer Wing Rack (w/ipad for control)
- *Stage Box- (1) Behringer S32 digital snake, (1) 24 channel analog snake
- *Main Speakers- (2) QSC K12.2 (2000w powered)
- *Stage Monitors-(2) QSC K8.2 (2000w powered)
- *Subwoofers- (2) QSC KS118 (3600w powered) built in front of stage
- *Fill- (1) QSC K8.2 (2000w powered)
- *Mics- (2) Shure SM58, (2) Shure SM48 (cardioid dynamic)
- *Mic Stands (3) K&M 21090.500 2 piece boom stand, (1) Sampson MB1 mini boom stand
- *Cables- (4) 25ft xlr, plus misc other cabling if needed
- *Lighting Control- Maestro DMX (autonomous lighting designer)
- *Front Stage Light Fixtures (2) PAR 18x 18W Zoom
- *Additional Light Fixtures- (1) Par 18 x 18w Zoom (over audience) (1) Moving Head LED Laser (over audience) (2) 8 x 12 RGBW LED Beam moving head fixture (back of stage)

- *Video Displays (2) 85" TCL LED TVs with USB-C to HDMI adapter (for sending display to both TVs at once with low latency)
 - Additional FX- (1) Chauvet Hurricane 1600 High Output Fog Machine
- *Backline Gear- (1) Hughes & Kettner Trilogy Guitar Head (4 Channel 100w)
- (1) Hughes and Kettner Vortex 412 Guitar Cabinet