

Technical Information

Canadian Part Numbers are shown in parentheses.

Model	Pt. #	Agent Capacity		UL/ULC Rating	Discharge Rate (lb/sec)	Discharge Time (Secs)	Discharge Range ft (m)	USCG Approval
10 HF ABC	11351 (11351ULC)	10 Lbs.	(4.54 kg)	1-A:20-B:C	1.11	10	30-40 ft (9.14-12.19m)	Type A Size II Type B:C Size II
10 HF PK	11651 (11651ULC)	10 Lbs.	(4.54 kg)	20-B:C	1.03	10	30-40 ft (9.14-12.19m)	Type B:C Size II
10 HF STD	11851 (11851ULC)	10 Lbs.	(4.54 kg)	10-B:C	1.17	9	30-40 ft (9.14-12.19m)	Type B:C Size II
13 HF ABC	11151 (11151ULC)	13.2 lbs. (6 kg)		1-A:10-B:C	1.26	11	40-50 ft (12.19-15.24m)	Type A Size II Type B:C Size II
13 HF PK	11251 (11251ULC)	13.2 lbs. (6 kg)		20-B:C	1.11	12	40-50 ft 40-50 ft (12.19-15.24m)	Type B:C Size II
13 HF STD	11451 (11451ULC)	13.2 lbs. (6 kg)		10-B:C	1.25	10	15.24m (12.19-15.24m)	Type B:C Size II
20 HDHF ABC	12351 (12351ULC)	20 lbs.	(9.07 kg)	4-A:60-B:C	1.17	18	40-50 ft (12.19-15.24m)	Type A Size II Type B:C Size III
20 HF PK	12651 (12651ULC)	20 lbs.	(9.07 kg)	60-B:C	1.57	13	40-50 ft (12.19-15.24m)	Type B:C Size III
20 HF STD	12851 (12851ULC)	20 lbs.	(9.07 kg)	60-B:C	1.34	14	40-50 ft (12.19-15.24m)	Type B:C Size III
30 HF ABC	13351 (13351ULC)	30 lbs.	(13.6 kg)	4-A:80-B:C	1.43	22	40-50 ft 40-50 ft (12.19-15.24m)	Type A Size II Type B:C Size IV
30 HF PK	13651 (13651ULC)	30 lbs.	(13.6 kg)	80-B:C	1.56	21	15.24m (12.19-15.24m)	Type B:C Size IV
30 HF STD	13851 (13851ULC)	30 lbs.	(13.6 kg)	40-B:C	1.75	17	40-50 ft (12.19-15.24m)	Type B:C Size IV