

| Model       | Part No. | Agent Type | Agent Capacity | UL/ULC Rating | Discharge Time | Discharge Range | Unit Wt. (lbs.) | Hose Length | Wheel Type               | Wheel Dims. Dia./Width |
|-------------|----------|------------|----------------|---------------|----------------|-----------------|-----------------|-------------|--------------------------|------------------------|
| OS A-50-SP  | 30360    | ABC        | 50 lbs.        | 10A:160B:C    | 36 sec.        | 25-35 ft.       | 154             | 25 ft.      | Rubber                   | 12.3 x 3.5 ins.        |
| OS A-150-SP | 31360    | ABC        | 125 lbs.       | 30A:240B:C    | 47 sec.        | 30-40 ft.       | 300             | 50 ft.      | Rubber                   | 16 x 4 ins.            |
| OS A-150-PT | 31490    | ABC        | 125 lbs.       | 30A:240B:C    | 43 sec.        | 30-40 ft.       | 325             | 50 ft.      | Rubber                   | 16 x 4 ins.            |
| OS A-150-RG | 31460    | ABC        | 125 lbs.       | 30A:240B:C    | 44 sec.        | 30-40 ft.       | 387             | 50 ft.      | Rubber                   | 16 x 4 ins.            |
| OS A-150-RG | 31470    | ABC        | 125 lbs.       | 30A:240B:C    | 44 sec.        | 30-40 ft.       | 422             | 50 ft.      | Steel                    | 36 x 2.5 ins.          |
| OS A-150-RG | 31480    | ABC        | 125 lbs.       | 30A:240B:C    | 44 sec.        | 30-40 ft.       | 434             | 50 ft.      | Steel Wheel Rubber Tread | 36 x 2.5 ins.          |
| OS A-350-PT | 32180    | ABC        | 300 lbs.       | 30A:320B:C    | 53 sec.        | 30-40 ft.       | 657             | 50 ft.      | Steel                    | 36 x 6 ins.            |
| OS A-350-PT | 32190    | ABC        | 300 lbs.       | 30A:320B:C    | 53 sec.        | 30-40 ft.       | 683             | 50 ft.      | Steel Wheel Rubber Tread | 36 x 6 ins.            |
| OS A-350-RG | 32160    | ABC        | 300 lbs.       | 30A:320B:C    | 52 sec.        | 30-40 ft.       | 780             | 50 ft.      | Steel                    | 36 x 6 ins.            |
| OS A-350-RG | 32170    | ABC        | 300 lbs.       | 30A:320B:C    | 52 sec.        | 30-40 ft.       | 806             | 50 ft.      | Steel Wheel Rubber Tread | 36 x 6 ins.            |
| OS K-50-SP  | 30760    | PK         | 50 lbs.        | 160B:C        | 36 sec.        | 25-35 ft.       | 154             | 25 ft.      | Rubber                   | 12.3 x 3.5 ins.        |
| OS K-150-SP | 31760    | PK         | 125 lbs.       | 320B:C        | 54 sec.        | 30-40 ft.       | 300             | 50 ft.      | Rubber                   | 16 x 4 ins.            |
| OS K-150-PT | 31590    | PK         | 125 lbs.       | 320B:C        | 54 sec.        | 30-40 ft.       | 325             | 50 ft.      | Rubber                   | 16 x 4 ins.            |
| OS K-150-RG | 31560    | PK         | 125 lbs.       | 320B:C        | 55 sec.        | 30-40 ft.       | 387             | 50 ft.      | Rubber                   | 16 x 4 ins.            |
| OS K-150-RG | 31570    | PK         | 125 lbs.       | 320B:C        | 55 sec.        | 30-40 ft.       | 422             | 50 ft.      | Steel                    | 36 x 2.5 ins.          |
| OS K-150-RG | 31580    | PK         | 125 lbs.       | 320B:C        | 55 sec.        | 30-40 ft.       | 434             | 50 ft.      | Steel Wheel Rubber Tread | 36 x 2.5 ins.          |
| OS K-350-PT | 32380    | PK         | 300 lbs.       | 320B:C        | 62 sec.        | 30-40 ft.       | 657             | 50 ft.      | Steel                    | 36 x 6 ins.            |
| OS K-350-PT | 32390    | PK         | 300 lbs.       | 320B:C        | 62 sec.        | 30-40 ft.       | 683             | 50 ft.      | Steel Wheel Rubber Tread | 36 x 6 ins.            |
| OS K-350-RG | 32360    | PK         | 300 lbs.       | 320B:C        | 57 sec.        | 30-40 ft.       | 780             | 50 ft.      | Steel                    | 36 x 6 ins.            |
| OS K-350-RG | 32370    | PK         | 300 lbs.       | 320B:C        | 57 sec.        | 30-40 ft.       | 806             | 50 ft.      | Steel Wheel Rubber Tread | 36 x 6 ins.            |
| OS W-65     | 76501    | Halotron   | 65 lbs.        | 4A:60B:C      | 20 sec.        | 15-25 ft.       | 252             | 25 ft.      | Rubber                   | 16 x 4 ins.            |
| OS W-150    | 71501    | Halotron   | 150 lbs.       | 10A:120B:C    | 30 sec.        | 23-36 ft.       | 396             | 50 ft.      | Rubber                   | 16 x 4 ins.            |

USCG APPROVED MODELS – 30360, 31360, 30760, and 31760