

Model	Pt. #	Agent Capacity	UL/ULC Rating	Discharge Rate (lb/sec)	Discharge Time (Secs)	Discharge Range ft (m)	USCG Approval
10 HDHF ABC	11350 (11350ULC)	10 Lbs. (4.54 kg)	1-A:20-B:C	1.11	10 sec	30-40 ft (9.14-12.19m)	Type A Size II Type B:C Size II
10 HDHF PK	11650 (11650ULC)	10 Lbs. (4.54 kg)	20-B:C	1.03	10	30-40 ft (9.14-12.19m)	Type B:C Size II
10 HDHF STD	11850 (11850ULC)	10 Lbs. (4.54 kg)	10-B:C	1.17	9	30-40 ft (9.14-12.19m)	Type B:C Size II
13 HDHF ABC	11150 (11150ULC)	13.2 lbs. (6 kg)	1-A:10-B:C	1.26	11	40-50 ft (12.19-15.24m)	Type A Size II Type B:C Size II
13 HDHF PK	11250 (11250ULC)	13.2 lbs. (6 kg)	20-B:C	1.11	12	40-50 ft 40-50 ft (12.19-15.24m)	Type B:C Size II
13 HDHF STD	11450 (11450ULC)	13.2 lbs. (6 kg)	10-B:C	1.25	10	(12.19-15.24m)	Type B:C Size II
20 HDHF ABC	12350 (12350ULC)	20 lbs. (9.07 kg)	4-A:60-B:C	1.17	18	40-50 ft (12.19-15.24m)	Type A Size II Type B:C Size III
20 HDHF PK	12650 (12650ULC)	20 lbs. (9.07 kg)	60-B:C	1.57	13	40-50 ft (12.19-15.24m)	Type B:C Size III
20 HDHF STD	12850 (12850ULC)	20 lbs. (9.07 kg)	60-B:C	1.34	14	40-50 ft (12.19-15.24m)	Type B:C Size III
30 HDHF ABC	13350 (13350ULC)	30 lbs. (13.6 kg)	4-A:80-B:C	1.43	22	40-50 ft 40-50 ft (12.19-15.24m)	Type A Size II Type B:C Size IV
30 HDHF PK	13650 (13650ULC)	30 lbs. (13.6 kg)	80-B:C	1.56	21	(12.19-15.24m)	Type B:C Size IV
30 HDHF STD	13850 (13850ULC)	30 lbs. (13.6 kg)	40-B:C	1.75	17	40-50 ft (12.19-15.24m)	Type B:C Size IV