

Model	Part No.	Agent Type	Agent Capacity	UL/ULC Rating	Discharge Time	Discharge Range	Shipping Wt. (lbs.)
OS 5 ABC	10960	ABC	5 lbs.	3A:40B:C	14 sec.	12-18 ft.	10 lbs.
OS 10 ABC	11360	ABC	10 lbs.	4A:80B:C	22 sec.	15-21 ft.	18.25 lbs.
OS 20 ABC	12360	ABC	20 lbs.	10A:120B:C	27 sec.	15-21 ft.	33.5 lbs.
OS 30 ABC	13360	ABC	30 lbs.	10A:160B:C	32 sec.	25-30 ft.	52.25 lbs.
OS 5 PK	11260	PK	5 lbs.	20B:C	9 sec.	12-18 ft.	10 lbs.
OS 10 PK	11760	PK	10 lbs.	80B:C	22 sec.	15-21 ft.	18.25 lbs.
OS 20 PK	12760	PK	20 lbs.	120B:C	27 sec.	15-21 ft.	33.5 lbs.
OS 30 PK	13760	PK	30 lbs.	160B:C	32 sec.	25-30 ft.	52.25 lbs.

All models are USCG Approved for marine vessel use when used in conjunction with the bracket specified on the label