

Technical Information

Maximum Local Application Height Above Hazard is 4 feet for all models

Model	MULTIPURPOSE (ABC) DRY CHEMICAL				HALOTRON	
Agent Type	ABC Dry Chemical	ABC Dry Chemical	ABC Dry Chemical	ABC Dry Chemical	Halotron I	Halotron I
Part #	80251	80521	81021	82021	87105	87205
Agent Capacity	2.5 lb. (1.13 kg)	5 lb. (2.3 kg)	10 lb. (4.5 kg)	20 lb. (9.1 kg)	18 lb. (8.2 kg)	25 lb. (11.3 kg)
Ship Weight	4 lb. (1.8 kg)	11 lb. (5 kg)	19 lb. (8.6 kg)	36 lb. (16.3 kg)	29 lb. (13.2 kg)	42 lb. (19 kg)
Operating Pressure	100 psi (689 kPa)	100 psi (689 kPa)	195 psi (1344 kPa)	195 psi (1344 kPa)	100 psi (689 kPa)	100 psi (689 kPa)
Unit Length	14.25 in (36.2 cm)	17.25 in (43.8 cm)	20.875 in (53 cm)	21.875 in (55.6 cm)	17.875 in (45.4 cm)	21.875 in (55.6 cm)
Unit Diameter	3.375 in (8.6 cm)	4.25 in (10.8 cm)	5.125 in (13 cm)	7.5 in (19.1 cm)	7 in (17.8 cm)	7.5 in (19.1 cm)
Max Total Flood Volume	120 cu. ft.	180 cu. ft.	1300 cu. ft.	2184 cu. ft.	500 cu. ft.	700 cu. ft.
Max Total Flood Height Above Hazard	7.5 ft.	7.5 ft.	13 ft.	14 ft.	8 ft.	10 ft.
Local Application Coverage Areas	4 ft. x 4 ft.	4 ft. x 6 ft.	10 ft. x 10 ft.	12 ft. x 13 ft.	4 ft. x 4 ft.	6 ft. x 6 ft.
Mounting Bracket	700287	700270	700226	700229	700228	700229