

Technical Information

Technical Information				Technical Information-2			
SP = Stored Pressure RG = Regulated Pressure PT = Pressure Transfer							
Canadian Part Numbers are shown in parentheses.							
MODEL	TYPE	PART NUMBER	AGENT CAPACITY	UL/ULC RATING	DISCHARGE TIME	DISCHARGE RANGE	UNIT WEIGHT
A-50-SP	ABC Dry Chemical	30010 (30015)	50 lb. (22.7 kg)	10-A:160-B:C	35 sec	25-35 ft. (7.6-10.7 m)	154 lb. (70 kg)
A-150-SP	ABC Dry Chemical	30110 (30115)	125 lb. (56.7 kg)	30-A:240-B:C	47 sec	30-40 ft. (9.1-12.2 m)	300 lb. (136 kg)
A-150-RG	ABC Dry Chemical	31120 (31125)	125 lb. (56.7 kg)	30-A:240-B:C	44 sec	30-40 ft. (9.1-12.2 m)	387 lb. (176 kg)
A-150-RG-36	ABC Dry Chemical	31140 (31145)	125 lb. (56.7 kg)	30-A:240-B:C	44 sec	30-40 ft. (9.1-12.2 m)	422 lb. (191 kg)
A-150-RG-36R	ABC Dry Chemical	31150 (31155)	125 lb. (56.7 kg)	30-A:240-B:C	44 sec	30-40 ft. (9.1-12.2 m)	434 lb. (197 kg)
A-150-PT	ABC Dry Chemical	31110 (31115)	125 lb. (56.7 kg)	30-A:240-B:C	43 sec	30-40 ft. (9.1-12.2 m)	325 lb. (147 kg)
A-350-RG	ABC Dry Chemical	32120 (32125)	300 lb. (136 kg)	30-A:320-B:C	52 sec	30-40 ft. (9.1-12.2 m)	780 lb. (354 kg)
A-350-RG-R	ABC Dry Chemical	32140 (32145)	300 lb. (136 kg)	30-A:320-B:C	52 sec	30-40 ft. (9.1-12.2 m)	806 lb. (366 kg)
A-350-PT	ABC Dry Chemical	32110 (32115)	300 lb. (136 kg)	30-A:320-B:C	53 sec	30-40 ft. (9.1-12.2 m)	657 lb. (298 kg)
A-350-PT-R	ABC Dry Chemical	32130 (32135)	300 lb. (136 kg)	30-A:320-B:C	53 sec	30-40 ft. (9.1-12.2 m)	683 lb. (310 kg)
S-150-RG	Standard Dry Chemical	31220 (31225)	150 lb. (68 kg)	240-B:C	48 sec	30-40 ft. (9.1-12.2 m)	412 lb. (187 kg)
S-150-RG-36	Standard Dry Chemical	31240 (31245)	150 lb. (68 kg)	240-B:C	48 sec	30-40 ft. (9.1-12.2 m)	447 lb. (203 kg)
S-150-RG-36R	Standard Dry Chemical	31250 (31255)	150 lb. (68 kg)	240-B:C	48 sec	30-40 ft. (9.1-12.2 m)	459 lb. (208 kg)
S-150-PT	Standard Dry Chemical	31210 (31215)	150 lb. (68 kg)	240-B:C	43 sec	30-40 ft. (9.1-12.2 m)	350 lb. (159 kg)
S-350-RG	Standard Dry Chemical	32220 (32225)	350 lb. (159 kg)	320-B:C	59 sec	30-40 ft. (9.1-12.2 m)	830 lb. (376 kg)
S-350-RG-R	Standard Dry Chemical	32240 (32245)	350 lb. (159 kg)	320-B:C	59 sec	30-40 ft. (9.1-12.2 m)	856 lb. (388 kg)
S-350-PT	Standard Dry Chemical	32210 (32215)	350 lb. (159 kg)	320-B:C	50 sec	30-40 ft. (9.1-12.2 m)	707 lb. (321 kg)
S-350-PT-R	Standard Dry Chemical	32230 (32235)	350 lb. (159 kg)	320-B:C	50 sec	30-40 ft. (9.1-12.2 m)	733 lb. (333 kg)
K-50-SP	Purple K Dry Chemical	30030 (30035)	50 lb. (22.7 kg)	160-B:C	34 sec	25-35 ft. (7.6-10.7 m)	154 lb. (70 kg)
K-150-SP	Purple K Dry Chemical	30310 (30315)	125 lb. (56.7 kg)	320-B:C	54 sec	30-40 ft. (9.1-12.2 m)	300 lb. (136 kg)
K-150-RG	Purple K Dry Chemical	31320 (31325)	125 lb. (56.7 kg)	320-B:C	55 sec	30-40 ft. (9.1-12.2 m)	387 lb. (176 kg)
K-150-RG-36	Purple K Dry Chemical	31340 (31345)	125 lb. (56.7 kg)	320-B:C	55 sec	30-40 ft. (9.1-12.2 m)	422 lb. (191 kg)
K-150-RG-36R	Purple K Dry Chemical	31350 (31355)	125 lb. (56.7 kg)	320-B:C	55 sec	30-40 ft. (9.1-12.2 m)	434 lb. (197 kg)
K-150-PT	Purple K Dry Chemical	31310 (31315)	125 lb. (56.7 kg)	320-B:C	54 sec	30-40 ft. (9.1-12.2 m)	325 lb. (147 kg)
K-350-RG	Purple K Dry Chemical	32320 (32325)	300 lb. (136 kg)	320-B:C	57 sec	30-40 ft. (9.1-12.2 m)	780 lb. (354 kg)
K-350-RG-R	Purple K Dry Chemical	32340 (32345)	300 lb. (136 kg)	320-B:C	57 sec	30-40 ft. (9.1-12.2 m)	806 lb. (366 kg)
K-350-PT	Purple K Dry Chemical	32310 (32315)	300 lb. (136 kg)	320-B:C	62 sec	30-40 ft. (9.1-12.2 m)	657 lb. (298 kg)
K-350-PT-R	Purple K Dry Chemical	32330 (32335)	300 lb. (136 kg)	320-B:C	62 sec	30-40 ft. (9.1-12.2 m)	683 lb. (310 kg)
Operating Temperature Range for all wheeled dry chemical extinguishers is -65° to 120°F (-54° to 49°C).							

Technical Information				Technical Information-2	
UNIT HEIGHT	UNIT WIDTH	UNIT DEPTH	HOSE LENGTH & DIAMETER	WHEEL TYPE	WHEEL DIAMETER
47 inches (119 cm)	24 inches (61 cm)	26.5 inches (67 cm)	25 ft. x .50 in. (7.6 m x 1.3 cm)	Rubber	12.3 in. x 3.5 in. (31.3 cm x 8.9 cm)
51 inches (128 cm)	26 inches (66 cm)	38 inches (96.5 cm)	50 ft. x .75 in. (15.2 m x 1.9 cm)	Rubber	16 in. x 4 in. (40.6 cm x 10.2 cm)
50 inches (127 cm)	24 inches (61 cm)	42 inches (105 cm)	50 ft. x .75 in. (15.2 m x 1.9 cm)	Rubber	16 in. x 4 in. (40.6 cm x 10.2 cm)
55 inches (139 cm)	32 inches (81.3 cm)	46 inches (117 cm)	50 ft. x .75 in. (15.2 m x 1.9 cm)	Steel	36 in. x 2.5 in. (91.4 cm x 6.4 cm)
55 inches (139 cm)	32 inches (81.3 cm)	46 inches (117 cm)	50 ft. x .75 in. (15.2 m x 1.9 cm)	Steel with rubber tread	36 in. x 2.5 in. (91.4 cm x 6.4 cm)
50 inches (127 cm)	24 inches (61 cm)	42 inches (105 cm)	50 ft. x .75 in. (15.2 m x 1.9 cm)	Rubber	16 in. x 4 in. (40.6 cm x 10.2 cm)
58 inches (147 cm)	36 inches (91.4 cm)	48 inches (122 cm)	50 ft. x 1 in. (15.2 m x 2.5 cm)	Steel	36 in. x 6 in. (91.4 cm x 15.2 cm)
58 inches (147 cm)	36 inches (91.4 cm)	48 inches (122 cm)	50 ft. x 1 in. (15.2 m x 2.5 cm)	Steel with rubber tread	36 in. x 6 in. (91.4 cm x 15.2 cm)
58 inches (147 cm)	36 inches (91.4 cm)	48 inches (122 cm)	50 ft. x 1 in. (15.2 m x 2.5 cm)	Steel	36 in. x 6 in. (91.4 cm x 15.2 cm)
58 inches (147 cm)	36 inches (91.4 cm)	48 inches (122 cm)	50 ft. x 1 in. (15.2 m x 2.5 cm)	Steel with rubber tread	36 in. x 6 in. (91.4 cm x 15.2 cm)
50 inches (127 cm)	24 inches (61 cm)	42 inches (105 cm)	50 ft. x .75 in. (15.2 m x 1.9 cm)	Rubber	16.4 in. x 4 in. (40.6 cm x 10.2 cm)
55 inches (139 cm)	32 inches (81.3 cm)	46 inches (117 cm)	50 ft. x .75 in. (15.2 m x 1.9 cm)	Steel	36 in. x 2.5 in. (91.4 cm x 6.4 cm)
55 inches (139 cm)	32 inches (81.3 cm)	46 inches (117 cm)	50 ft. x .75 in. (15.2 m x 1.9 cm)	Steel with rubber tread	36 in. x 2.5 in. (91.4 cm x 6.4 cm)
50 inches (127 cm)	24 inches (61 cm)	42 inches (105 cm)	50 ft. x .75 in. (15.2 m x 1.9 cm)	Rubber	16 in. x 4 in. (40.6 cm x 10.2 cm)
58 inches (147 cm)	36 inches (91.4 cm)	48 inches (122 cm)	50 ft. x 1 in. (15.2 m x 2.5 cm)	Steel	36 in. x 6 in. (91.4 cm x 15.2 cm)
58 inches (147 cm)	36 inches (91.4 cm)	48 inches (122 cm)	50 ft. x 1 in. (15.2 m x 2.5 cm)	Steel with rubber tread	36 in. x 6 in. (91.4 cm x 15.2 cm)
58 inches (147 cm)	36 inches (91.4 cm)	48 inches (122 cm)	50 ft. x 1 in. (15.2 m x 2.5 cm)	Steel	36 in. x 6 in. (91.4 cm x 15.2 cm)
58 inches (147 cm)	36 inches (91.4 cm)	48 inches (122 cm)	50 ft. x 1 in. (15.2 m x 2.5 cm)	Steel with rubber tread	36 in. x 6 in. (91.4 cm x 15.2 cm)
47 inches (119 cm)	24 inches (61 cm)	26.5 inches (67 cm)	25 ft. x .50 in. (7.6 m x 1.3 cm)	Rubber	12.3 in.. x 3.5 in. (31.3 cm x 8.9 cm)
51 inches (128 cm)	26 inches (66 cm)	38 inches (96.5 cm)	50 ft. x .75 in. (15.2 m x 1.9 cm)	Rubber	16 in. x 4 in. (40.6 cm x 10.2 cm)
50 inches (127 cm)	24 inches (61 cm)	42 inches (105 cm)	50 ft. x .75 in. (15.2 m x 1.9 cm)	Rubber	16 in. x 4 in. (40.6 cm x 10.2 cm)
55 inches (139 cm)	32 inches (81.3 cm)	46 inches (117 cm)	50 ft. x .75 in. (15.2 m x 1.9 cm)	Steel	36 in. x 2.5 in. (91.4 cm x 6.4 cm)
55 inches (139 cm)	32 inches (81.3 cm)	46 inches (117 cm)	50 ft. x .75 in. (15.2 m x 1.9 cm)	Steel with rubber tread	36 in. x 2.5 in. (91.4 cm x 6.4 cm)
50 inches (127 cm)	24 inches (61 cm)	42 inches (105 cm)	50 ft. x .75 in. (15.2 m x 1.9 cm)	Rubber	16 in. x 4 in. (40.6 cm x 10.2 cm)
58 inches (147 cm)	36 inches (91.4 cm)	48 inches (122 cm)	50 ft. x 1 in. (15.2 m x 2.5 cm)	Steel	36 in. x 6 in. (91.4 cm x 15.2 cm)
58 inches (147 cm)	36 inches (91.4 cm)	48 inches (122 cm)	50 ft. x 1 in. (15.2 m x 2.5 cm)	Steel with rubber tread	36 in. x 6 in. (91.4 cm x 15.2 cm)
58 inches (147 cm)	36 inches (91.4 cm)	48 inches (122 cm)	50 ft. x 1 in. (15.2 m x 2.5 cm)	Steel	36 in. x 6 in. (91.4 cm x 15.2 cm)
58 inches (147 cm)	36 inches (91.4 cm)	48 inches (122 cm)	50 ft. x 1 in. (15.2 m x 2.5 cm)	Steel with rubber tread	36 in. x 6 in. (91.4 cm x 15.2 cm)
Operating Temperature Range for all wheeled dry chemical extinguishers is -65° to 120°F (-54° to 49°C).					