



Portable Fire Extinguishers

10 LB. STANDARD STORED PRESSURE FIRE EXTINGUISHER

DESCRIPTION

Buckeye's 10 lb. Standard (aka Regular) Fire Extinguisher is a high performance fire extinguisher utilizing a sodium bicarbonate-based extinguishing agent, one of the most effective agents for Class B and Class C fires.

Typical uses: For flammable liquid hazards in public areas such as offices, classrooms, multi-family residences, and parking garages. For flammable liquid fires in commercial operations such as industrial facilities, sanitation facilities, vehicle service centers, and healthcare facilities.

FEATURES

- Manufactured in accordance with ANSI/UL 299 and ANSI/UL 711 Standards.
- US COAST GUARD approved for Type B:C Size II when used in conjunction with Mounting Bracket Model 809, P/N 700226.
- DOT and TC Compliant
- Polyester epoxy powder coated steel cylinder with all-metal valve assembly, operating lever, and handle.
- Color coded pressure gauge for easy verification of pressure status.
- Trilingual labels; English, Spanish, and French.
- Rechargeable for repeated usage.
- Standard dry chemical is available in 50 lb. Pails for recharging Buckeye extinguishers.

SPECIFICATIONS

Agent Capacity	10 lbs. / 4.54 kg
UL/ULC Rating	40-B:C
Shipping Weight	18.25 lbs. / 8.3 kg
Height	21 in / 53.3 cm
Width	7.75 in / 19.7 cm
Cylinder Diameter	5.125 in / 13 cm
Discharge Time	14 seconds
Discharge Range	15-21 ft. / 4.6-6.4m
Operating Temperature Range	-65° F to 120° F -54° C to 49° C
Operating Pressure	195 psi

ORDERING INFORMATION

10 LB Standard Dry Chemical Fire Extinguisher with Wall Hook

Part No. 11840

Note: For Coast Guard Approval, you must also order the Model 809 Mounting Bracket, P/N 700226

Refer to the Buckeye Spare Parts List for replacement parts



📍 110 Kings Road, Kings Mountain, NC 28086-0428

☎ 704-739-7415 📠 704-739-7418 🌐 www.buckeyef.com