

The "STREAKER"

By

CESTAD



Now a fully-suspended 8-hp. Terrain Cycle. Features two hand-operated external band type non-reversing brakes for fast, sure stops. Big 18.5/9.50-8" rear tires for traction and a mag front wheel for looks.

Thick padded vinyl seats team up with shock absorbing suspension to smooth out the bumpiest terrain. With a 12-volt alternator for producing power for the head and tail lights you can enjoy your new Terrain Cycle day or night.



And here's all the horsepower you need to horse around. All of the features above PLUS a 290 cc - 2 cyl. - 24 hp. Kohler engine. Ride in comfort and safety surrounded by a heavy duty tubular frame with roll cage and frame mounted gas tank. With independent front and rear suspension, it handles like a dream at speeds up to 55 mph.

The "STREAKER"

Models CS-918A/924A

SPECIFICATIONS

ENGINE	918A	924A
Manufacturer	Tecumseh	Kohler
H.P. @ RPM	8 h.p. @ 3850 rpm	24 h.p. @ 6500 rpm.
Type	1 cylinder—4 cycle	2 cylinder—2 cycle
Starter type	manual recoil type	manual recoil type
Fuel capacity	1 gallon	2 gallons
Estimated running time	2 hours	2½ hours
Fuel requirement	regular gas	92 octane pre-mixed w/SAE 30 or up oil

TRANSMISSION (DRIVE TRAIN)

Type—torque converter
Primary Drive—V-belt symmetric
Clutch—centrifugal pulley
Final Drive—#40 chain
Drive Ratios—CS-918A—19.17 low—7.39 high
 —CS-924A—16.2 low—5.88 high
Axle—Automotive type differential w/steel sprocket and bevel gears—
1-in. dia. axles.

CHASSIS

Frame Type—single backbone tubular reinforced w/roll cage—shock
mount superstructure
Wheelbase—65¼"
Width—52¾" overall; 43¼" tread width.
Overall length—85"
Suspension—shock absorber swing axle (rear), dual shock (front).
Wheels—front—6" dia. x 3" wide, 2-piece mag.
 rear—8" dia. x 7" wide, pressed steel demountable.
Overall height—38¾" (roll bar).
Seat—two-piece, vinyl covered, foam padded, plywood reinforced.
Tires—front—5.30/4.50-6; 2 ply; universal tread, tube type.
 rear—18.5/9.50-8; 2 ply; turf tread; tubeless.
Brakes—dual, independently operated, band type, non-reversing.
Ground clearance—5¼"
Seat height—14"
Handle bar height—34"
Lighting system—12 volt regulated, headlight and taillight.
Trailer hitch—equipped with tongue-type hitch.

ATTACHMENTS AVAILABLE (ACCESSORIES)

Emergency/Parking brake mounted on jackshaft (918A only).
Electric start option (918A only).
Ski attachment.
Fiberglass body.

WEIGHTS AND DIMENSIONS

	918A	924A
Dry weight	245 lbs.	285 lbs.
Shipping weight	300 lbs.	340 lbs.
Carton dimensions	37" high x 45½" wide x 65½" long w/skid	



Central States



TOOL & DIE WORKS

4301-19 N. 30TH STREET OMAHA NEBRASKA 68111

Printed in U.S.A.

From OldMiniBikes.com