



Hytera Communications Corporation Limited Stock Code: 002583.5Z

Address: Hytera Tower, Hi-Tech Industrial Park North, 9108# Beihuan Road, Nanshan District, Shenzhen, P.R.C.









Hytera retains right to change the product design and specification. Should any printing mistake occur, Hytera doesn't bear relevant responsibility. Little difference between real product and product indicated by printing materials will occur by printing reason.

HYT, Hytera are registered trademarks of Hytera Communications Corp., Ltd. © 2023 Hytera Communications Corp., Ltd. All Rights Reserved.

Hytera DMR Professional Two-way Radio and Repeater Solution Catalog





Hytera DMR Professional Two-way Radio and Repeater Solution

Professional DMR Two-way Radios

Professional DMR Portable Two-way Radio

Professional DMR Mobile Two-way Radio

DMR Repeater

Dual-mode Rugged Radio

Extended Pseudo Trunk System

Smart Dispatch Plus System

DMR Trunking SCADA Solution

Specifications



Hytera DMR Professional Two-way Radio and Repeater Solution

Professional DMR Two-way Radios

>> Professional DMR Portable Two-way Radio

HP7 SERIES

Overview

HP7 series starts from innovation and conducts breakthrough design and development in appearance and function. With its ultra-clear audio, ultra-strona battery, ultra-fast response. ultra-light weight and solid reliability, it brings more reliable, more efficient and more reliable and to comfortable communication experience industry users.

Highlights

Thinner and lighter

An optimized mechanical design and a compact lithium polymer battery are discreetly made to fit into the HP7 series design, making the radio thinner and lighter, easy to carry.

Louder and clearer audio

HP7 series equips an optimized powerful loudspeaker that can help users to hear clear sounds even in a noisy environment. Water-porting technology is also used to drain out any water that gets into the speaker cavity, ensuring the audio clarity is maintained. Al-based noise cancellation technology can decrease 30dB background noise and howling. No matter what noise environment the calling party is in, it ensures that the called party hears a clear sound.

More intuitive and efficient

HP78X brings a large screen and a brand new intuitive UI to make the operation more efficient. The 2.4-inch colour screen can display more information (i.e. 6 contacts) per page. Its Quick Access Menu allows users to set the radio faster. Messages are listed in conversation for guick reading and review. The Interface Switcher is added to the option of programmable buttons, allowing guick switch between up to four frequently accessed interfaces.

Standard

Accessories





Adapter(12V/1A)





Li-polymer battery 2400mAh







delivering key information and calls.

Higher level of ruggedness

Longer battery life

Hp7 series is designed as per the MIL-STD-810H. It is IP68

rated, impervious to water jets and submersible to a depth

of 2 meters for 4 hours, and also resilient to 2-meter drop

onto concrete. No matter where the mission drives the

officer, the HP7 series is the partner to count on, because it

HP7 series optimizes product design and technologies to

reduce power consumption, meanwhile the latest in proven

lithium polymer technology is used in the standard battery

which is lighter and smaller than ever before. The new

technologies bring a duty cycle of 5/5/90 on achieving a

shift life of 24 hours (standard battery) / 30 hours (optional

battery) on high transmit power and ensure a full day of

can stand up to the toughest environment.

Optional





BT wireless ring PTT



BT Wireless remote speaker microphone





Multi-unit charger

HP6 SERIES

Overview

HP6 series integrates lightweight appearance design, perfect functional design and professional manufacturing process. It has beautiful appearance, clear voice, and easy to use. It can make users work easier and more focused, organize and operate more orderly and efficiently, which is ideal for communication.

Highlights

Light and stylish

The streamlined HP6 series is compact and light for easy carrying and wearing.

Rugged and durable

Wear-resistant and heat-resistant PC material, and the back surface is anti-slip textured. Being manufactured as per the MIL-STD-810H standard, the HP6 series is IP67 rated and resilient to 2-meter drop to stand up to a lot of wear and tear.

Ultra clear audio

It has louder and clearer audio though the leading Al-based voice enhancement technology that decreases the unwanted background noise and howling.

Powerful battery

A lithium polymer battery, small and light, yet with high capacity is installed to the HP6 series, delivering a duty cycle * Subsequent BT version upgrades are subject to no of 5/5/90 on achieving a shift life of 20 hours (standard further notice, and the right of interpretation battery) / 30 hours (optional battery) on high transmit power.

Extended range

Thanks to the improved receiver sensitivity, the HP6 series provides better connectivity both in marginal areas of coverage and indoors. This will deliver improved safety and operational benefits for operatives in the field.

Simple and practical

Larger PTT button, dual-feature knob, flexible programmable buttons, built-in low-power BT 5.2 supports a variety of accessory connections.

belongs to our company.

Accessories

Standard











speaker microphone







Optional



(USB port)



2400mAh

BT wireless ring PTT







3000mAh

HP5 SERIES

Overview

HP5 series is a new-gen professional portable two-way radio that provides reliable voice communications for high-end office buildings, stadiums, industrial parks, schools, hospitals. and more. The universal Type-C port makes programming. upgrading, and charging more convenient than ever before. Durable enough to withstand dust, heat, shock and water submersion, the HP5 series is IP67 and MIL-STD-810H certified. The superior audio has never been compromised, thanks to the powerful speaker and the Al-based noise cancellation algorithm. The outstanding sensitivity ensures stable communications in challenging environments.

Highlights

Crisp, clear audio

Purify your voice, and eliminate the noise. The HP5 series delivers crystal-clear audio in any environment, thanks to Albased noise cancellation. This technology suppresses any annoving feedback howling and filters out the unwanted ambient noises. So you can feel like talking face to face in every call no matter where you are.

Versatile type-c port

Just share the same USB data cable with your smartphone, then you can charge your radio with a power bank or car charger, or program and upgrade your radio. All of these benefit from the universal Type-C port.

Rugged reliability

The HP5 series is built to withstand the harsh conditions that come with all kinds of industry fieldwork. The radio housing is made of polycarbonate with excellent abrasion and heat resistance. And the texture on the back of the radio is non-slip design. More importantly, this tough radio is IP67-rated and meets stringent MIL-STD-810H military standards for protecting against dust, water, vibrations, 1.5-meter drops, extreme temperatures, and more.

Accessories

Standard







Adapter(12V/1A)



Li-polymer battery 1500mAh







always keep connected.

Bt, wirelessly, conveniently

Break through the distance

your smartphone.

Easier to use

The HP5 series has optional BT 5.2 capability, so you can

experience total freedom with no cords when using BT

audio accessories. This feature also allows you to pair the

radio with your smartphone, and then get radio

programming done by the HyTool Radio Manager app on

The HP5 series has dedicated dual knobs for volume and

channel controls, improving your efficiency. The U-shaped

slot on the back of the battery allows you to install or

remove the belt clip more easily. The enlarged LED indicator

makes you know radio status at a glance, no matter

whether the radio is in your hand, on your shoulder or waist.

When you go further out, you may encounter degraded

communications due to weak radio signal. With the 0.18µV

(-122dBm) sensitivity, the HP5 series provides exceptional

communication coverage. It ensures reliable

communications even at the far edge of coverage with

weak signal. Wherever you go in the workplace, you can

Optional



BT Wireless earniece



Programming cable (USB port)



BT wireless ring PTT



speaker microphone



Multi-unit charaer



3000mAh

PD98X

Overview

As a new generation digital trunking radio, it uses top-notch digital noise-cancelling technologies, which ensures clear and crisp voice quality even in noisy environments. It features full duplex call for bi-directional communication between radios. The built-in BT 4.0 module exhibits lower power consumption, faster transmit rate, and more wireless connection function. You can separately order smart battery and corresponding charger, with which the charging time is reduced to half. It supports call recording and local information inquiry over conventional network, facilitating backtrace of call processing method. With its MIL-certified feature and IP68 protection, the radio is fully accommodate to various harsh conditions.



Highlights

Noise-cancelling technology

Use completely new noise-cancelling technology, which guarantees voice quality in noisy environments.

IP68 protection

IP68 dust and waterproof standard ensures outstanding performance even in harsh environments.

Built-in BT 4.0 module for efficient and convenient application

PD98X has built in BT 4.0, which not only supports audio transmission, but also data transmission, such as programming via BT etc.

Single frequency repeater mode

Based on interference cancellation technique, PD98X can use one slot to receive signal and the other to transmit it in the same frequency at the same time in DMO mode to extend communication distance.

Full duplex call

PD98X can make full duplex call with PD98X, telephone or cell phone.

Optional Accessories



Remote Speaker Microphone (IP57)

System









3-Wire Surveillance Farniece with Transparent Acoustic Tube (beige)





Switchina Powe



(USB Port)





Battery Optimizina



2-wire Farpiece with (for Thick Battery) Earpiece with TransparentWireless Earphone and Acoustic Tube(Black) Neck Loop(Beige)





Overview

X1p is constructed in compact style with a thickness of only 23 mm(1400mAh), which facilitates carrying and operation. It uses 1.8" transflective 65536 color display which is still readable in sunlight. All afore-mentioned features combined with its IP67 protection facilitate it the primary option for users.



Highlights

Dual modes

The radio can operate in analog mode and digital mode for a smooth analog-to-digital migration.

Reliable and durable

Compliant with MIL - STD - 810 C/D/E/F/G and IP67 certified.

Compact structure

Comfortable-to-touch metal frame makes the radio ideal for leadership, undercover, and decision-making personnel.

Superior audio quality

With narrowband codec and digital error-correction technologies, X1p delivers superior voice under noisy environments.

Advanced encryption

The radio supports AES encryption algorithm and 256-digit dynamic encryption keys to secure communication.

Ease of use

The radio is as thin as 23 mm(1400mAh) and can work with wireless headsets, collar microphone. palm controller and flexible antenna.

Accessories

Standard



Li-ion Battery



Power Adapter rapid-charger MCU



dual-Pocket





Optional



Belt clip



3-Wire Surveillance Earniece with Transparent Acoustic Tube (beige)



HM78X

Overview

It is a flexible and highly scalable DMR digital mobile radio. The product is flexible in form, supports single, split and fixed platforms, and can be applied to various environments, including vehicles, motorcycles, fixed control rooms and ships, providing efficient communication between partners. The product supports a variety of connections, expands rich applications, and facilitates integration into existing businesses to improve your work efficiency.

>> Professional DMR Mobile Two-way Radio



Highlights

Reliable and durable

The quality of the whole machine conforms to MIL-STD-810H With the flexible control heads and accessories, the HM78X and IP54 industrial protection standards, and can play an can be installed in various environments to satisfy different excellent role in various harsh working environments.

Longer communication distance

leading level in the industry. It can ensure the timely transmission and diffusion of key information in a larger area. and further ensure the personal safety of users and **Ethernetinterface** organizational efficiency.

Clear and loud sound quality

adopted, which can effectively reduce environmental noise station network interface, etc. and echo, and improve speech intelligibility.

Flexible deployment

user requirements, the connection cable of the remote control head can be either 3m, 10m or 40m as standard. a connection cable of up to 100m is also available (single head). Digital receiving sensitivity increased to 0.18 µV. Reach the it support standard integrated control head, remote single/dual control head and desktop fixed station.

It can transmit the communication data of on-board stations through IP link, and has a variety of application schemes, such as IP interconnection between on-board Professional AI intelligent noise elimination technology is stations, secondary development based on on on-board

Accessories

Standard



Conventional model: palm microphone without keypad



Trunking model: palm microphone without keypad







Model with GPS GPS antenna

Optional



DB26 connector external speaker



10-pin connector desktop microphone



Power supply for mobile radio





Programming cable DB26 Connector foot PTT DB26M-DB9M







radio and repeater to realize cross-brand for wireless link solution (VHF UHF) or cross mode(analog digital) communication





Antenna



Power supply of fixed BT Wireless remote station cabinet



speaker microphone



HM68X/HM65X

Overview

The HM6 series is the new generation entry-level professional DMR mobile two-way radio designed to provide reliable voice and data communication in the vehicle anytime. Compact and liahtweight, the radio is easy to install. Thanks to the handheld control head (HHCH), you can install the HM6 series unit anywhere in your vehicle such as in the trunk and still control the radio. With the ergonomic design, the four piano-style buttons make operations effortless. The Al-based noise cancellation ensures the HM6 series to deliver superb clear audio without ambient noise. With the higher RX sensitivity, the HM6 series provides you with smoother communication. Thus you can always stay connected with your teammates anywhere you move. The HM6 series is born to be your best partner in transportation, business, utilities, and more.

Highlights

Smoother communication

Thanks to the high RX sensitivity, the HM6 series can deliver clear and dependable communications even in areas where the signal is unstable or weak.

Wireless connection

With the built-in BT 5.0 module, the HM6 Series can work with the BT audio accessories to boost your safety and productivity during in-vehicle communications. And these radios can be programmed through BT, saving time and resource.

Crystal-clear audio

The HM6 series delivers superb audio in noisy streets or highways. The Al-based noise cancellation filters out echoes and background noises such as horn and engine sounds, making you hear and be heard in the conversation. The howling suppression prevents the screeching or howling feedback between two radios in the same vehicle, ensuring clear and uninterrupted communication on the move.

Accessories

Standard



Microphone Without Display(HM68X) With Display(HM65X)



Remote Speaker





Mounting Bracket Kit



Handheld control head

Superior durability

Unrivaled versatility

your safety and productivity.

With the HHCH connected, the HM6 series can be installed

under the seat, in the trunk, or anywhere in the vehicle,

making the installation more flexible. Also, the HHCH helps

you turn on or off the HM6 Series, switch channels or

The HM6 series withstands harsh temperatures, shock, and

vibration, and meets MII -STD-810H standards, and IP54 for

dust and water intrusion. The connection between the

palm microphone and 10pin aviation connector keep very

tight and is difficult to loosen. The drawstring of the palm

microphone has the excellent stretching ability to protect

Except for reliable voice calls, the HM6 series provides

various data services including text message, clarity

transmission, emergency alarm, radio enable/disable, GPS

location, and more. These services dramatically enhance

the palm microphone to get the maximum service life.

contacts, adjust volumes, or view messages.

GPS antenna

Optional



External power supply Ignition cable



Rluetooth remote speaker microphone



data cable



DB26 Programming



and data Cable

USB Programming/ downloading firmware upgrading cable

>> DMR Repeater

HR106X

Overview

The HR106X Ultra-thin DMR Repeater is the next generation in creative style and functionality that elevates the industry standard in professional two-way radios. The HR106X is the new state-of-the-art in digital radio communications. providing a more efficient experience with loud and clear audio, support for multiple types of radio and communications systems, and extended range. The HR106X features AC and DC auto-switching power, two simultaneous TDMA voice channels, high performance cooling, all in a compact 1U form factor



Highlights

Economical 1u structure

The 1U height of HR106X makes it compact, reducing space requirements for installation which is quite helpful especially when deploying the repeater in vehicle with limit space such as SUV(Sport Utility Vehicle).

Ac/Dc auto switch

HR106X equipped built-in power adapter support 100-240V AC power supply that reduce the deployment cost and support also the backup battery which connected to DC input port. The repeater can charge the backup batteries during AC power supply.

Cost-effective network construction

The enhanced version of HR106X is integrated with router and SIP gateway features. Less devices and simplified management. It offers a cost-effective solution for your network construction.

Convenient management

In the enhanced version a web-based back end platform has been designed to simplify repeater management. Configuration, upgrade and real-time diagnosis can all be completed through a web browser, which is ideal for remote management.

Wide coverage

The communication range of HR106X series is extended with enhanced Rx sensitivity. And the Ethernet port enables access to IP networks, which provides the capability for the HR106X to connect everyone and everywhere. Users can connect multiple repeaters to cover larger areas.

Accessories

Standard





Optional



DR26-DR26 cable connects two



DR26-DR9 cable connects mobile repeater for backup radio and repeater for function



connects two repeter to realize cross-band (VHF-UHF)or cross mode(analog-digital) communication





Feeder connects external duplexer

and repeater



1/2 RF feeder



link solution

DC power cable connects to vlagus

HR65X

It is the new generation business-ready digital repeater designed to expand the communication range of your DMR radios. High performance and high reliability, the repeater ensures consistent, reliable, seamless voice and data communications your team need most. It is a top pick for hotels, office buildings, supermarkets, industrial parks, and more. Compact and lightweight, the repeater can be flexibly mounted to the wall or carried on the back by tailored accessories, uncompromising with on-site installation conditions. The rugged structure makes the repeater stand up to harsh environments. The repeater allows the communication connection anywhere you need.

Highlights

Flexible deployment

The innovative structure design gives the repeater unprecedented outlook and lightweight performance. With the compact body and the built-in duplexer, the repeater consider the space conservation properly. The tailored matching installation accessories achieve the very flexible installation on the sites with very limited conditions. You can realize the site construction as long as there is a wall or a limited piece of plane. When you work outside, the weight only about 2 kg makes the repeater effortless to carry on the back. Thus to reduce the transportation burden and cost greatly. For the scenario of indoor coverage, the raido super slim size minimize site requirement and deliver digital services to each of your work floors.

High reliability

The repeater is built to outperform in harsh environment. It Smooth transision conforms to MIL-STD-810H standards for ruggedness, and is IP67 rated (for 10 W version) or IP54 (for 25 W version) for dust and water intrusion.

battery, the repeater can keep running in the event of apower ideal solution for you to migrate smoothly from outage. When it connects to the AC power supply, the battery analog to digital with minimal disruption and works as a backup. In case of the outage, the 12.5Ah battery is investment.



ready to power the repeater for up to nine hours at 10 W output or four hours at 25 W output with a 50% duty cycle. Moreover, benefiting from the latest fast charging technology, the battery can be fully charged in just 3.5 hours. The repeater gives you a durable communication with time extension.

IP multi-site connect

From the small region single site DMR conventional system, to large region IP Multi-site system, the repeater delivers powerful and stable signal to every corner of your workplace. It can also interconnect with other Hytera repeaters, building a tailored network to meet your variable requirements.

The repeater can operate in analog mode, DMR mode, or dynamic mixed digital/analog mode, which automatically switches between analog and digital Designed to operate on AC power source or an optional based on the call it receives. This repeater is the

Accessories

Standard

Optional

















Programming cable



External duplexer cable



Wall Mount Bracket Kit

RD98XS 100W

Overview

The RD98XS 100W High-power DMR Repeater Pro is at the heart of analogue and digital radio networks. With outstanding functionality and high reliability, it can support up to 100W transmission power, this repeater overcomes signal obstruction to greatly expand the range of the radio system, ensuring reliable communication over a longer distance.



With 100W transmit power output, RD98XS 100W can

dramatically enlarge your communication range, provide a

investment. And the Ethernet port enables the access of IP

network, which provides the capability for RD98XS 100W to

Highlights

Compact design

Though integrated with the built-in high power amplifier, RD98XS 100W still remains the compact 2U height structural design which is very easy and flexible to install in different huge area coverage while reducing your network cabinets, and reduces numerous concerns for installation.

High cooling capacity

The power amplifier can dissipate most generated heat with extraordinary efficiency. In addition, the integrated fan system ensures stable and powerful operation.

User friendly

Thanks to the high-resolution display, programmable buttons and clear LED indicators. the RD98XS 100W is extremely easy to use, whether during ongoing operations, or during maintenance tasks.

Accessories

Standard



Optional



Palm Microphone (IP67)



Back to Back



Bracket for



Bracket for PS22002(L) (2U)(black) PS22002(L) (2U)(grey)



cable (USB)

Wide coverage

connect everyone everywhere.



Db26 data cable (USB)







Power Supply for RD98XS(50W PS22002(L)

Dual-mode Rugged Radio

PDC680

All in one All in control Mission critical focused

Hytera PDC680 dual-mode rugged radio combines a missioncritical DMR radio with an Android-based smartphone in a single device. It harnesses the power of narrowband and broadband technologies to provide mission-critical voice call, photo and video taking, positioning, and more. This innovative radio enables seamless communications between DMR network and public network such as 2G, 3G, LTE, and WLAN. As a professional rugged radio, the PDC680 is engineered for effortless usability. The ergonomic design on smart knob and keys and the modular design on UIs make it easy for you to accomplish tasks with one hand.



Highlights

All-in-one device

With highly integrated and modular design, the PDC680 combines a DMR radio and a smartphone into a single device. So you do not need to carry two separate handsets for accessing voice, data, video, and more.

Precise positioning

The PDC680 provides fast and accurate positioning to track people or devices, indoor and outdoor. The GPS, Galileo, GLONASS, QZSS, BDS, and A-GPS are used for outdoor positioning, while the location-based service (LBS) and WLAN are adopted for indoor positioning.

Automatic switch

The PDC680 can automatically switch between DMR network and LTE network. Registering with both networks using the same ID, the PDC680 can always select the optimal one to deliver smooth and reliable voice communications everywhere, indoors or out.

Live streaming

capture on-site pictures and videos, and then send them to another radio or command center in real time to dramatically improve situational awareness. The PDC680 also supports the external camera.

Purpose-built app

With the Android system, the PDC680 can support systemlevel apps developed by Hytera and other third-party apps. This helps you communicate and respond efficiently.

Loud and clear audio

Using the enlarged front chamber technology and professional acoustic design, the PDC680 can output sound at up to 128 dB. To ensure crystal and clear audio in noisy environments, the PDC680 adopts Al-based noise cancellation, echo cancellation, and wind noise reduction technologies.

Rugged and durable

Rated at IP68 and ESD IEC Level 4, the PDC680 withstands water, dust, and electrostatic discharge. It can also withstand 1.5-meter drop from all angles. The industrialgrade touchscreen stands up to continuous use in any weather. All these help the PDC680 perform well in harsh environments.

All-round security assurance

The PDC680 can secure the voice and data through authentication, software and hardware encryption, or more. TrustZone protects the system; full-disk encryption (FDE) protects the user data; air interface encryption (AIE) Thanks to the dual HD cameras, the PDC680 allows you to and end-to-end encryption (E2EE) protect the voice and data communication; and remote control helps you manage radios.

Smart management

You can remotely manage radios in batches, including upgrade programming, permission control, key configuration, app management, device health management, and data backup and recovery.

Specifications

DMR/Analog 340-470MHz 136-174MHz								
LTE		DMR/Analog	340-470MHz 136-174MHz					
TDD-LTE: B34/B38/B39/B40/B41 CDMA CDMA 1xRTT BC0 CDMA2000 1xEV-D0 BC0 WCDMA B1/B2/B4/B5/B8 GSM 850/900/1800/1900MHz WLAN 802.11 a/b/g/n/ac, 2.4GHz/5GHz NFC (Optional) 13.56MHz BT V4.2, BDR/EDR/BLE GPS/BDS/GLONASS/Galileo/QZSS/A-GPS Position performance for open zone: TTFF (Cold boot) < 1minute Horizontal accuracy<5m(95% probable at -130dB) Weight (with antenna & bottery) Weight (with antenna & Android 10.0 & bottery) Google Certification Ports 13PIN Accessory/Charging Port Screen Top Screen: 0.92" Color: black & white Main Screen: 3.6" 1280x720, Color depth: 24bit Camera Rear Camera: 13MP, Auto Focus			3GPP LTE					
Wireless Data Communication Wireless Data Communication WCDMA B1/B2/B4/B5/B8 GSM 850/900/1800/1900MHz WLAN 802.11 a/b/g/n/ac, 2.4GHz/5GHz NFC (Optional) 13.56MHz BT V4.2, BDR/EDR/BLE GPS/BDS/GLONASS/Galileo/QZSS/A-GPS Positioning Position performance for open zone: TTFF (Cold boot) < 1minute Horizontal accuracy<5m(95% probable at -130dB) Weight (with antenna &battery) Weight (with antenna &battery) Google Certification Ports 13PIN Accessory/Charging Port Camera Screen Top Screen: 0.92" Color: black & white Main Screen: 3.6" 1280x720, Color depth: 24bit Front Camera: 13MP, Auto Focus Rear Camera: 13MP, Auto Focus Rear Camera: 13MP, Auto Focus 2x Nano SIM card Namory Rouse Autor of Narrowband Operating 7,74/(netal)		LTE	FDD-LTE: B1/B2/B3/B4/B5/B7/B8/B20/B26/B28					
Wireless Data Communication Wireless Data Communication WCDMA B1/B2/B4/B5/B8 GSM 850/900/1800/1900MHz WLAN 802.11 a/b/g/n/ac, 2.4GHz/5GHz NFC (Optional) 13.56MHz BT V4.2, BDR/EDR/BLE GPS/BDS/GLONASS/Galileo/QZSS/A-GPS Positioning Positioning Position performance for open zone: TTFF (Cold boot) < 1minute Horizontal accuracy<5m(95% probable at -130dB) Weight (with antenna &battery) Weight (with antenna &battery) Google Certification Ports 13PIN Accessory/Charging Port Camera Front Camera: 3MP, Fixed Focus Rear Camera: 13MP, Auto Focus 2x Nano SIM card Namory Top Card Slots 1x Micro SD card 1x Encryption card for Narrowband Operating 7,7//(netad)			TDD-LTE: B34/B38/B39/B40/B41					
Wireless Data Communication WCDMA B1/B2/B4/B5/B8 GSM 850/900/1800/1900MHz WLAN 802.11 a/b/g/n/ac, 2.4GHz/5GHz NFC (Optional) 13.56MHz BT V4.2, BDR/EDR/BLE GPS/BDS/GLONASS/Galileo/QZSS/A-GPS Positioning Positioning Dimensions (H x W x D) Weight (with antenna &battery) Weight (with antenna &battery) Weight (with antenna &battery) Google Certification General Specifications General Specifications Camera Memory Front Camera: 3MP, Fixed Focus Rear Camera: 13MP, Auto Focus 2x Nano SIM card 1x Micro SD card 1x Encryption card for Narrowband Operating 7,71/(Insted)		CDMA	CDMA 1xRTT BC0					
Wireless Data Communication GSM 850/900/1800/1900MHz WLAN 802.11 a/b/g/n/ac, 2.4GHz/5GHz NFC (Optional) 13.56MHz BT V4.2, BDR/EDR/BLE GPS/BDS/GLONASS/Galileo/QZSS/A-GPS Positioning Positioning Dimensions (H x W x D) Weight (with antenna &battery) Weight (with antenna &battery) Weight (with antenna &battery) Google Certification Ports 13PIN Accessory/Charging Port Screen General Specifications General Specifications Camera Front Camera: 3MP, Fixed Focus Rear Camera: 13MP, Auto Focus		CDIVIA	CDMA2000 1xEV-DO BC0					
Communication GSM 850/900/1800/1900MHz WLAN 802.11 a/b/g/n/ac, 2.4GHz/5GHz NFC (Optional) 13.56MHz BT V4.2, BDR/EDR/BLE GPS/BDS/GLONASS/Galileo/QZSS/A-GPS Positioning Positioning Dimensions (H x W x D) Weight (with antenna & battery) Weight (with antenna & battery) Google Certification General Specifications General Specificati	Wireless Data	WCDMA	B1/B2/B4/B5/B8					
WLAN NFC (Optional) NFC (Optional) BT V4.2, BDR/EDR/BLE GPS/BDS/GLONASS/Galileo/QZSS/A-GPS Positioning Positioning Dimensions (H x W x D) Weight (with antenna &battery) Google Certification Ports 13PIN Accessory/Charging Port Screen Camera Memory Memory Memory Memory Front Camera: BMP, Fixed Focus Rear Camera: 13MP, Auto Focus 2x Nano SIM card 1x Micro SD ca		GSM	850/900/1800/1900MHz					
Positioning Positioning Positioning Positioning Positioning Positioning Position performance for open zone: TTFF (Cold boot) < Iminute Horizontal accuracy<5m(95% probable at -130dB) Weight (with antenna &battery) Weight (with antenna &battery) Google Certification Ports 13PIN Accessory/Charging Port Screen Top Screen: 0.92" Color: black & white Main Screen: 3.6" 1280x720, Color depth: 24bit Front Camera: 8MP, Fixed Focus Rear Camera: 13MP, Auto Focus Rear Camera: 15MP, Auto Focus	001111101110011011	WLAN	802.11 a/b/g/n/ac, 2.4GHz/5GHz					
Positioning GPS/BDS/GLONASS/Galileo/QZSS/A-GPS Position performance for open zone: TTFF (Cold boot) < 1minute Horizontal accuracy < 5m(95% probable at -130dB) Dimensions (H x W x D) Weight (with antenna &battery) Weight (with antenna &battery) Google Certification Ports 13PIN Accessory/Charging Port Screen Top Screen: 0.92" Color: black & white Main Screen: 3.6" 1280x720, Color depth: 24bit Camera Rear Camera: 13MP, Auto Focus		NFC (Optional)	13.56MHz					
Positioning Position performance for open zone: TTFF (Cold boot) < 1minute Horizontal accuracy<5m(95% probable at -130dB) Dimensions (H x W x D) Weight (with antenna &battery) Weight (with antenna &battery) Google Certification Ports 13PIN Accessory/Charging Port Screen Top Screen: 0.92" Color: black & white Main Screen: 3.6" 1280x720, Color depth: 24bit Memory Front Camera: 8MP, Fixed Focus Rear Camera: 13MP, Auto Focus Rear Camera: 13MP, Card Rear Camera: 13MP, Auto Focus Rear Camera: 13MP, Auto Focus Rear Camera: 13MP, Auto Focus Rear Camera: 13MP, Card Rear Camera: 13MP, Auto Focus Rear Camera: 13MP, Auto Focus Rear Camera: 13MP, Card Rear Camera: 13MP, Auto Focus Rear Camera: 13MP, Card Rear Camera: 13MP,		BT	V4.2, BDR/EDR/BLE					
TTFF (Cold boot) < 1minute Horizontal accuracy<5m(95% probable at -130dB) Dimensions (H x W x D) Weight (with antenna &battery) Weight (with antenna &battery) Google Certification Ports 13PIN Accessory/Charging Port Screen Top Screen: 0.92" Color: black & white Main Screen: 3.6" 1280x720, Color depth: 24bit Front Camera: 8MP, Fixed Focus Rear Camera: 13MP, Auto Focus Rear Camera: 13MP, Color depth: 24bit Rear Camera: 13MP, Auto Focus			GPS/BDS/GLONASS/Galileo/QZSS/A-GPS					
TTFF (Cold boot) < 1minute Horizontal accuracy<5m(95% probable at -130dB) Dimensions (H x W x D) Weight (with antenna & battery) Weight (with antenna & Android 10.0 & battery) Google Certification Ports 13PIN Accessory/Charging Port Top Screen: 0.92" Color: black & white Main Screen: 3.6" 1280x720, Color depth: 24bit Front Camera: 8MP, Fixed Focus Rear Camera: 13MP, Auto Focus 2x Nano SIM card Card Slots 7xW(Pated)		Positionina	Position performance for open zone:					
Dimensions (H x W x D) Weight (with antenna & battery) Weight (with antenna & battery) Google Certification Ports 13PIN Accessory/Charging Port Top Screen: 0.92" Color: black & white Main Screen: 3.6" 1280x720, Color depth: 24bit Memory Front Camera: 8MP, Fixed Focus Rear Camera: 13MP, Auto Focus Rear Camera: 13MP, Color depth: 24bit 7.7 Williams Top Screen: 0.92" Color: black & white Main Screen: 3.6" 1280x720, Color depth: 24bit Memory Front Camera: 8MP, Fixed Focus Rear Camera: 13MP, Auto Focus 2x Nano SIM card 1x Micro SD card 1x Encryption card for Narrowband Operating 7.7 Williams		1 ositioning	TTFF (Cold boot) < 1minute					
(H x W x D) Weight (with antenna & battery) Weight (with antenna & battery) Weight (with antenna & battery) Google Certification Ports 13PIN Accessory/Charging Port Top Screen: 0.92" Color: black & white Main Screen: 3.6" 1280x720, Color depth: 24bit Memory Front Camera: 8MP, Fixed Focus Rear Camera: 13MP, Auto Focus Rear Camera: 13MP, Camera: 13MP, Auto Focus Rear Camera: 13MP, Camera: 13MP, Auto Focus Rear Camera: 13MP, Camera: 13MP, Camera: 13MP, Auto Focus Rear Camera: 13MP, Camera: 13MP, Camera: 13MP, Auto Focus Rear Camera: 13MP,			Horizontal accuracy<5m(95% probable at -130dB)					
(with antenna &battery) Weight (with antenna &battery) Google Certification Ports 13PIN Accessory/Charging Port Top Screen: 0.92" Color: black & white Main Screen: 3.6" 1280x720, Color depth: 24bit Camera Front Camera: 8MP, Fixed Focus Rear Camera: 13MP, Auto Focus Rear Camera: 13MP, Auto Focus Rear Camera: 13MP, Auto Focus Rear Camera: 13MP, Auto Focus Rear Camera: 13MP, Auto Focus Rear Camera: 13MP, Auto Focus Rear Camera: 13MP, Auto Focus 2x Nano SIM card 1x Micro SD card 1x Encryption card for Narrowband Operating 7.7V/(petad)			140mm x 60mm x 29.1mm					
&battery) Weight (with antenna &battery) Google Certification Ports 13PIN Accessory/Charging Port Top Screen: 0.92" Color: black & white Main Screen: 3.6" 1280x720, Color depth: 24bit Camera Front Camera: 8MP, Fixed Focus Rear Camera: 13MP, Auto Focus Memory Front Camera: 8MP, Fixed Focus Rear Camera: 13MP, Auto Focus 2x Nano SIM card Card Slots 1x Micro SD card 1x Encryption card for Narrowband Operating 7,71/(Insted)		Weight						
Weight (with antenna &battery) Google Certification Ports 13PIN Accessory/Charging Port Top Screen: 0.92" Color: black & white Main Screen: 3.6" 1280x720, Color depth: 24bit Camera Front Camera: 8MP, Fixed Focus Rear Camera: 13MP, Auto Focus Rear Camera: 13MP, C		(with antenna	325g±5g					
(with antenna &battery) Google Certification Ports 13PIN Accessory/Charging Port Top Screen: 0.92" Color: black & white Main Screen: 3.6" 1280x720, Color depth: 24bit Camera Front Camera: 8MP, Fixed Focus Rear Camera: 13MP, Auto Focus Rear Camera: 13MP, Camera:		& battery)						
&battery) Google Certification Ports 13PIN Accessory/Charging Port Screen Top Screen: 0.92" Color: black & white Main Screen: 3.6" 1280x720, Color depth: 24bit Camera Front Camera: 8MP, Fixed Focus Rear Camera: 13MP, Auto Focus Rear Camera: 13MP, Camera: 13MP, Auto Focus 2x Nano SIM card 1x Micro SD card 1x Encryption card for Narrowband Operating 7,71/(Pated)		Ü						
Google Certification Ports 13PIN Accessory/Charging Port Top Screen: 0.92" Color: black & white Main Screen: 3.6" 1280x720, Color depth: 24bit Camera Front Camera: 8MP, Fixed Focus Rear Camera: 13MP, Auto Focus Rear Camera: 13MP, Camera: 13MP, Auto Focus 2x Nano SIM card 1x Micro SD card 1x Encryption card for Narrowband Operating 7.71/(Pated)			Android 10.0					
General Specifications General Specifications Screen Top Screen: 0.92" Color: black & white Main Screen: 3.6" 1280x720, Color depth: 24bit Camera Front Camera: 8MP, Fixed Focus Rear Camera: 13MP, Auto Focus 2x Nano SIM card 1x Micro SD card 1x Encryption card for Narrowband Operating 7,7//(Detail)								
General Specifications Top Screen: 0.92" Color: black & white Main Screen: 3.6" 1280x720, Color depth: 24bit Camera Front Camera: 8MP, Fixed Focus Rear Camera: 13MP, Auto Focus Front Camera: 8MP, Fixed Focus Rear Camera: 13MP, Auto Focus 2x Nano SIM card Card Slots 1x Micro SD card 1x Encryption card for Narrowband Operating 7,7//(Detail)		Ÿ	Google Mobile Services					
Specifications Screen Main Screen: 3.6" 1280x720, Color depth: 24bit Camera Front Camera: 8MP, Fixed Focus Rear Camera: 13MP, Auto Focus 2x Nano SIM card Card Slots 1x Micro SD card 1x Encryption card for Narrowband Operating 7,71/(Ipsted)		Ports	13PIN Accessory/Charging Port					
Main Screen: 3.6"1280x720, Color depth: 24bit Camera Front Camera: 8MP, Fixed Focus Rear Camera: 13MP, Auto Focus Front Camera: 8MP, Fixed Focus Rear Camera: 13MP, Auto Focus 2x Nano SIM card Card Slots 1x Micro SD card 1x Encryption card for Narrowband Operating 7,77/(Insted)		Screen	Top Screen: 0.92" Color: black & white					
Rear Camera: 13MP, Auto Focus Memory Front Camera: 8MP, Fixed Focus Rear Camera: 13MP, Auto Focus 2x Nano SIM card Card Slots 1x Micro SD card 1x Encryption card for Narrowband Operating 7,7//(Detail)	Specifications	Screen	Main Screen: 3.6" 1280x720, Color depth: 24bit					
Rear Camera: 13MP, Auto Focus Memory Front Camera: 8MP, Fixed Focus Rear Camera: 13MP, Auto Focus 2x Nano SIM card 1x Micro SD card 1x Encryption card for Narrowband Operating 7,77/((leted))		Camera	Front Camera: 8MP, Fixed Focus					
Rear Camera: 13MP, Auto Focus 2x Nano SIM card Card Slots 1x Micro SD card 1x Encryption card for Narrowband Operating 7,77/((loted))			,					
2x Nano SIM card Card Slots 1x Micro SD card 1x Encryption card for Narrowband Operating 7,7//(Dated)		Memory	·					
Card Slots 1x Micro SD card 1x Encryption card for Narrowband Operating 7.7//(Detect)		,	-					
1x Encryption card for Narrowband Operating 7.77/(Dated)		0 101 1						
Operating 7.7//Pated		Cara Siots						
		Operating	ix Encryption card for Narrowband					
Voltage 7.7V (Ratea)			7.7V (Rated)					
Standard: 2400 mAh		Dattasu	Standard: 2400 mAh					
Battery Optional: 4000 mAh		bullery	Optional: 4000 mAh					

		Channel Spacing	25/20/12.5kHz					
	Transceiver	TX Power	UHF: 1W/4W					
			VHF: 1W/5W					
	nvironment	Dust and Water	IEC60529- IP68 (2m, 4h) IEC60529- IP66					
		ESD	IEC 61000-4-2 (Level 4), ±8 kV (Contact), ±15 kV (Air)					

Accessories

Standard

















Li-Poly Battery

Optional

Wireless Remote PTT&MIC Controller Speaker Microphone



Swivel Earset









Extended Pseudo Trunk System

Overview

Extended Pseudo Trunk is a new distributed trunking system solution developed by Hytera, which is based on Pseudo Trunk technology and combined with advantages of digital trunking system.

Highlights

Outstanding features

Extended Pseudo Trunk system possesses advantages and features of the digital conventional system and provides such special features as Dedicated Data Channel, Dynamic Authentication, Priority Interrupt, Inter-site Group Call, Multisite Handover, Priority Call etc.

Significant reduction of call conflicts

Extended Pseudo Trunk system uses the mechanism "Request and Permit" to allocate channels. The radio transmits or receives services only after the data handshake is successful. This ensures the radio not to stay on a wrong channel due to call conflict, and prevents interference from a radio with strong signal.

Cost-effective system

Conventional system can be upgraded to Extended Pseudo Trunk system via software, protecting the existing investments.

High flexibility

Extended Pseudo Trunk system can be used with dispatching system, phone system, XNMS (Extended Network Management System) to increase its flexibility.

Strong fault-tolerant capability

Extended Pseudo Trunk system automatically detects failures and takes measures to minimize the influences, ensuring proper repeater services in fault tolerance mode.

Dedicated control channel not required

By sharing logic channels of the repeater, Extended Pseudo Trunk system allows the radios to communicate via all repeaters in the site. There is no need for specific control channels, thus the channel utilization is increased.

Advanced load balancing

Extended Pseudo Trunk system allocates different groups to different home repeaters to minimize call conflicts on the same repeater and improves success rate of call access.



Large capacity

The Extended Pseudo Trunk network based on HR106X (DMR version 2.5) supports up to 30 sites.

Each Extended Pseudo Trunk single-site system based on HR106X (DMR version 2.5) supports up to 12 voice repeaters and 8 data repeaters.

The Extended Pseudo Trunk network composed of a mixture of RD9 and HR106X supports up to 16 sites. Each Extended Pseudo Trunk single-site system composed of a mixture of RD9 and HR106X supports up to 8 voice repeaters and 8 data repeaters.

Smart Dispatch Plus System

Overview

Hytera Smart Dispatch Plus is designed for DMR conventional radio network with efficient communication, management and dispatching functions. Characterized by C/S structure, modularized design and supporting VoIP, Hytera Smart Dispatch Plus delivers you an enhanced dispatching platform with high scalability and robustness.



Highlights

Flexible deployment

Smart Dispatch Plus adopts a modular design and consists of server, client, and gateway. It can be flexibly deployed based on user's requirements.

- Server, gateway and client can be installed on a same computer.
- Server, gateway and client can also be deployed in different places.
- Both repeaters and mobile radios can directly connect with Smart Dispatch Plus.

Rich service

- Various kind of voice service: individual call, group call, all call, dispatcher intercom, sip call, voice recording, etc.
- · Short message, timed message, Email access.
- Location service: Real-time track and historical playback, Gen-fencing, overspeed / underspeed alarm, POI, etc.
- Safety service: Disable/enable, remote monitor, lone worker and emergency alarm.

High efficiency applications

- Work order management
- Telemetry
- OTAP (Over the air programming)

User-friendly

- Graphical interface for easy operation and management
- Support multiple languages
- Support RTL (Right to Left) input


DMR Trunking SCADA Solution

Overview

Hytera DMR Trunking SCADA Solution is designed for telemetry and data communication, it offers a secure and reliable wireless data transmission solution based on the DMR Tier III trunking standard.

Hytera DTM-6000 is a dedicated data modern that provides wide coverage data communication and abundant data services for power industry users, allowing different devices such as RTUs, PLCs and meters to interface with SCADA systems through IP/Ethernet or serial ports. Providing full support for industry standard protocols such as IEC60870-5-101, IEC60870-5-104, DNP3 and Modbus.

Architecture



Hytera SCADA gateway: connected to SCADA control center. Transfer the DMR protocol to SCADA protocol.

DMR data modem: connected to RTU with IP/Ethernet port and serial port, transfer the SCADA protocol to DMR protocol.

Highlights

Voice&Data in one system

On the basis of providing reliable and efficient data communication, Hytera DMR Trunking SCADA Solution provides excellent voice dispatching capability from DMR standard, providing individual call, group call, broadcast call, PSTN call and other trunking voice call related features to meet different aspects of requirements and scenarios.

High efficiency data transmission ability

Any traffic channel can be configured as dedicated SCADA data transmission channel according to end user's need so as to guarantee data priority and realize the load balance. Hytera provides end to end encryption for data transmission.

Dual timeslots data transmission is one of innovative features, it combines 2 timeslots in the same channel unit for data transmission, improving the efficiency of data transmission, doubling the speed of data transmission.

Multiple data modem interfaces

Supporting IP/Ethernet and serial ports concurrent communication in a network. A single modem could provide various interfaces for industrial equipments.

Large coverage

Hytera DMR trunking base station offers large and reliable coverage with higher terminal output power, the maximum output power of data modem is 25W. In this way, with less base stations, a certain area can be covered, the number of required base station will be fewer and the construction investment will be saved.

High priority for emergency data

Together with End to End QoS Solution, data traffic would be categorized with priorities to ensure high priority data like alarm message can be delivered to host in time.

Easy modem configuration and maintenance

The network management system provides configuration management, performance management, fault management and firmware version management of the data modem.

Security services

This system supports End-to-end Encryption (E2EE) mode, in which data is transferred in form of cipher text and protected during the entire transfer process before reaching the SCADA Gateway and the DMR modem. The data is encrypted or decrypted at the SCADA Gateway and DMR modem through the Advanced Encryption Standard (AES 128 or 256) Encryption algorithms and then sent to the SCADA system.

Key Componets



Туре	HP78X	HP70X	HP68X	HP60X	HP56X	HP50X	HM78X	HM68X	HM65X	HR106X	HR65X
Frequency Range	UHF1: 400-470MHz UHF3: 350-400MHz VHF: 136-174MHz	UHF1: 400-470MHz UHF3: 350-400MHz VHF: 136-174MHz	VHF1: 136-174MHz	UHFm: 400-527MHz VHF1: 136-174MHz	VHF1: 136-174MHz	UHF1: 400-470MHz VHF1: 136-174MHz	UHF1:400-470MHz UHF3:350-400MHz VHF1:136-174MHz UHF5:806-941MHz	VHF1: 136-174MHz	VHF1: 136-174MHz	UHF1:400-470MHz VHF:136-174MHz UHF2:450-527MHz	UHF1: 400-470MHz
Zone Capacity	64	64	64	64	32	16	64	16	16	1	1
Channel Capacity	1024	1024	1024	1024	512	256	1024	512	512	1024	1024
Display	2.4 inch color LCD, 240*320, 10 Line	0.91 inch OLED	transflective LCD, 1.8 inch	0.91 inch OLED	1.45 inch LCD, 240 x320 pixels, colorful, 6 line display	NA	2.4 inch, 8 Line	1.45 inch,6 Line	NA	Nixie tube display	Nixie tube display
Keypad	Full	NA	Full	NA	Half	NA	Half	Half	NA	1	1
Dedicated Emergency Button	Support	Support	NA	NA	NA	NA	Support	Support	NA	1	1
Programmable Buttons	6	2	5	2	7	2	7	2	NA	1	1
Dust and Water Intrusion	IP66,IP68	IP68	IP67,IP68	IP67,IP68	IP67	IP67	IP54	IP54	IP54	1	25W: IP54 10W: IP67
Humidity	MIL-STD 810H	MIL-STD 810H	MIL-STD 810H	MIL-STD 810H	MIL-STD 810H	MIL-STD 810H	MIL-STD-810G	MIL-STD-810G	MIL-STD-810G	1	MIL-STD 810H
Shock and Vibration	MIL-STD 810H	MIL-STD 810H	MIL-STD 810H	MIL-STD 810H	MIL-STD 810H	MIL-STD 810H	MIL-STD-810G	MIL-STD-810G	MIL-STD-810G	1	MIL-STD 810H
Analog Conventional Mode	Support	Support	Support	Support	Support	Support	Support	Support	Support	Support	Support
MPT-1327 Trunking	NA	NA	NA	NA	NA	NA	NA	NA	NA	NA	NA
Digital Conventional Mode	Support	Support	Support	Support	Support	Support	Support	Support	Support	Support	Support
IP Site Connect	Optional(Roaming)	Optional(Roaming)	Optional(Roaming)	Optional(Roaming)	Optional(Roaming)	Optional(Roaming)	Optional(Roaming)	Optional(Roaming)	Optional(Roaming)	Optional	Optional
XPT Trunking	Support	Support	Support	Support	Optional (single site)	Optional (single site)	Support	Optional	Optional	Optional	NA
DMR Tier III Trunking	Optional	Optional	NA	NA	NA	NA	Optional	NA	NA	NA	NA
Integrated Wi-Fi	NA	NA	NA	NA	NA	NA	NA	NA	NA	/	1
GPS	Optional	Optional	Optional	Optional	Optional	Optional	Optional	Optional	Optional	/	Optional
Integrated GLONASS	Optional	Optional	Optional	Optional	Optional	Optional	Optional	NA	NA	/	1
Vibration	Support	Support	Support	Support	NA	NA	1	1	1	/	1
Bluetooth	Optional 5.2	Optional 5.2	Optional 5.2	Optional 5.2	Optional 5.2	Optional 5.2	Optional 5.0	Optional 5.0	Optional 5.0	1	1
Lone Worker	Support	Support	Support	Support	Support	Support	Support	Support	Support	1	1
Man-down	Support	Support	Support	Support	NA	NA	1	1	1	1	1
RFID Board	NA	NA	NA	NA	NA	NA	1	1	1	/	1
TF Card	Support (8G/16G)	Support (8G/16G)	NA	NA	NA	NA	Support	1	1	1	1
Option Board	Support	Support	NA	NA	NA	NA	Support	1	1	1	1
Type-C Port	NA	NA	NA	NA	Support	Support	NA	NA	NA	NA	NA
Noise Cancellation	Support	Support	Support	Support	Support	Support	Support	Support	Support	Support	Support
Over The Air Programming	Support	Support	Support	Support	NA .	NA	Support	NA	NA .	Support	Support
HyTool Radio Manager	NA	NA	Support	Support	coming soon	coming soon		1	1	1	1
Water-porting Design	Support	Support	NA	NA	NA	NA				1	
Ethernet Port	1	1	1	1	1	1	Support	1	1	Support	Support
Remote Control Head			1	1	1		Support			1	
Router	1	1	1	1	1	1	1		1	Support	1
SIP Gateway		1	1		1					Support	
Web-Based Management	1	1	1	1	1	1	1	1	1	Support	1