



iC 90

Fetal & Maternal
Monitor

iC 90 Fetal & Maternal Monitor

Features:

- Portable, easy operation & elegant design ;
- 12 inches TFT foldable color screen ;
- Basic parameters: FHR, TOCO, AFM, maternal SpO2, HR, NIBP, ECG, RESP, TEMP ;
- Advanced Digital Signal Processing (DSP) Technique is applied for Real-time Calculation and Mode Identification ;
- Help to improve efficiency by sorting out the traces that require closer analysis by obstetrician ;
- A standard patient event marker and a clinical event marking button to separately mark clinical events ;
- Provide convenience and reliability during antepartum, intrapartum and postpartum monitoring ;
- Continuous monitoring during transport ;
- Alarm system: time-over alarm, non-paper alarm, out of range FHR alarm ;
- High sensitivity FHR transducer, high signal-to-noise ratio ;
- 24 hours CTG storage, fast review and print ;
- Unique design for cable of transducers to avoid intertwinning ;
- Wire or wireless connect to central monitoring system ;
- Automatically adjust thermal paper 150mm/152mm ;
- High capability rechargeable Li-ion battery lasting 4 hours.

Options:

- Twins FHR measurement
- Build-in network/PC connecting interface
- FAS(fetal acoustic stimulator)
- Wireless network

Specification:

Fetal Heart Rate

Transducer: Multi-crystals, pulsed doppler
high sensitivity

Strength: <5mW/cm2

Working frequency: 1.0MHz

Measurement range: 50~210 bpm

TOCO

Measurement range: 0~100 units

Auto Fetal Movement (AFM): Automatic detection

SpO2

Measurement range : 70%~100%.

Accuracy: $\pm 3\%$

HR

Measurement range: 30bpm~240bpm
Accuracy: ± 2 bpm

NIBP

Systolic pressure: 50~240mmHg

Diastolic pressure: 25~200mmHg

Mean pressure: 15~180mmHg

Measure mode: Manual

ECG

Heart Rate Measurement and

Alarm Range: 15-300bpm

Accuracy: ± 1 bpm

Input: 5-lead ECG cable

Sweep Speed: 25 mm/s

Amplitude Selection: x1/4, x1/2, x1, x2, x4

Temperature

Measurement and Alarm Limit: 0-50°C

Probe: Skin surface

Accuracy: $\pm 0.1^\circ\text{C}$ (25°C ~45°C),

$\pm 0.2^\circ\text{C}$ (0°C ~25°C or 45°C ~50°C)

Respiration

Measurement Mode: Thoracic Impedance

Respiration Rate: 0-150 bpm

Waveform Display Speed: 25mm/s

Power: A.C.100-240v, 50/60Hz or 16.8v Li-ION battery

Power Consumption: < 20W

Dimension: 350mm×320mm×85mm (L×W×H)

Net weight:3.5 kg



Shenzhen Biocare Electronics Co., Ltd.



Add: Floor 6, Main Building, High-tech Innovation Park Baoan, Shenzhen, 518102, P.R.China

Tel: +86 755 27960641

Fax: +86 755 27960643

E-mail: sales@biocare.com.cn

<http://www.biocare.com.cn>