

S&G® 2890B SCIF Door Lock

**BUILT TO THE STRICT REQUIREMENTS
OF FEDERAL SPECIFICATION FF-L-2890B**




**2890B exterior with
2740B dial lock (inset)**
Types I through IV shown

The S&G 2890B is highly engineered to ensure the security of SCIFs used by U.S. agencies, DoD and defense contractors. Equipped with single motion egress, the S&G 2890B allows for intuitive and safe egress from inside a SCIF. Working in conjunction with both GSA-approved combination locks, the S&G 2890B provides the highest level of safety and security.


FEATURES:

- **FLEXIBLE DESIGN:** Interfaces with both electromechanical combination locks that meet Federal Specification FF-L-2740B, including the S&G 2740B and X-10.
- **STURDY INSTALLATION:** Heavy-duty, adjustable mounting system provides a strong, solid install that prevents door collapse.
- **FIELD ADJUSTABLE:** Configures with right-hand, left-hand, in-swing and out-swing doors made of metal or wood.
- **SMOOTH OPERATION:** Heavy-duty, surface mounted strike with integral roller for secure, smooth operation.
- **PINCH-PROOF STRIKES:** Available for in-swing, out-swing and double door applications.
- **LASTING DURABILITY:** Levers tested to 1M cycles and panic bar to 500K cycles for reliability and longevity.
- **MODULAR DESIGN:** All configurations are based on the same modular platform, providing a faster, standardized installation.
- **HIGHEST FIRE RATING:** 3-hour UL fire rating that is highest on the market in this segment.


VERSATILE MOUNTING OPTIONS




#1 STRIKE
(Single or double door in-swing mortise)
PRODUCT NO. 2890-601



#2 STRIKE
(Single door out-swing)
PRODUCT NO. 2890-602



#3 STRIKE
(Single or double door in-swing surface)
PRODUCT NO. 2890-603



#9 STRIKE
(Double door out-swing surface)
PRODUCT NO. 2890-609

2890B SCIF Lock

2890B (Interior)	FF-L-2890B Classification/ S&G P/N	Life Safety NFPA 101 and ADA Single-Motion Egress	Access Control Capability	Retracted Lock Bolt Block
	Type I (PDPL) 2890-410	 Exit Lever	Mechanical	 Keyed cam lock
	Type II (PDPL) 2890-420	 Exit Lever	Mechanical and Electronic	 Keyed cam lock
	Type III (PDLAP) 2890-430	 Panic Bar	Mechanical	 Keyed cam lock
	Type IV (PDLAP) 2890-440	 Panic Bar	Mechanical and Electronic	 Keyed cam lock
	Type V (ADB) 2890-450	 Exit Lever	None	 Keyed cam lock
	Type VI (ADB) 2890-460	 Exit Lever	None	 Keyless thumbturn

PDPL: Pedestrian Door Preassembled Lock
PDLAP: Pedestrian Door Lock Assembly Panic
ADB: Auxiliary Deadbolt

All part numbers listed include all necessary hardware, except for a FF-L-2740B GSA combination lock or keyed rim cylinder. All units shipped with a #2 strike. Alternate strikes sold separately.

For a 5-year warranty, all six types can be installed with an S&G 2740B high-security lock (sold separately). Installing 2890B with X-10 provides 2-year warranty. 3-Hour UL Fire Rated with either combination lock.

Inquire about other available options, including a panic bar kit for 4' doors and a 2890B-style exit only device.

www.sargentandgreenleaf.com/2890B
www.stanleysecuritysolutions.com

Corporate Headquarters: One Security Drive • Nicholasville, Kentucky 40356 • USA • Tel. 859-885-9411, Fax 859-887-2057

Except as otherwise noted, all trademarks in this data sheet are trademarks of Stanley Black and Decker or its affiliates in the U.S. and elsewhere. ® denotes a trademark registered in the U.S. Patent and Trademark Office.

Patents Pending.

SECURE YOUR REPUTATION WITH SARGENT AND GREENLEAF®

Sargent and Greenleaf safe and vault locks have been protecting the assets of banks, businesses and governments for more than 150 years. The S&G 2890B represents the latest design advances to produce a single motion egress SCIF door lock that provides the highest level of security.

