

818 KGF



VF1

DIMENSION		SPECIFICATIONS		CLAMPING RATE	
LENGTH	276 mm	STRENGTH	818 kgf	STEEL	2,4 - 4,8
HEIGHT	270 mm	AIR PRESSURE	5-7 bar	ALUMINIUM	2,4 - 4,8
WEIGHT	1,10 kg	STROKE	20 mm	STAINLESS STEEL	2,4 - 4,8

Ürün	Ölçü	Ağırlık	Kuvvet	Hava Basıncı	Stroke	Çelik	Alüminyum	Paslanmaz
S1	276x270	1,10 kg	818 kgf	5-7 bar	20 mm	2,4 - 4,8	2,4 - 4,8	2,4 - 4,8
S2	276x312	1,50 kg	918 kgf	5-7 bar	20 mm	2,4 - 5,0	2,4 - 5,0	2,4 - 5,0
S3	276x312	1,70 kg	1497 kgf	5-7 bar	26 mm	3,0 - 6,4	3,0 - 6,4	3,0 - 6,4
S4	276x312	1,86 kg	1904 kgf	6-7 bar	20 mm	4,8 - 6,4	4,8 - 6,4	4,8 - 6,4



VF2

918 KGF

DIMENSION		SPECIFICATIONS		CLAMPING RATE	
LENGTH	276 mm	STRENGTH	918 kgf	STEEL	2.4 - 5.0
HEIGHT	312 mm	AIR PRESSURE	5-7 bar	ALUMINIUM	2.4 - 5.0
WEIGHT	1.50 kg	STROKE	20 mm	STAINLESS STEEL	2.4 - 4.0

Ürün	Ölçü	Ağırlık	Kuvvet	Hava Basıncı	Stroke	Çelik	Alüminyum	Paslanmaz
S1	276x270	1.10 kg	818 kgf	5-7 bar	20 mm	2.4 - 4.8	2.4 - 4.8	2.4 - 4.8
S2	276x312	1.50 kg	918 kgf	5-7 bar	20 mm	2.4 - 5.0	2.4 - 5.0	2.4 - 5.0
S3	276x312	1.70 kg	1497 kgf	5-7 bar	26 mm	3.0 - 6.4	3.0 - 6.4	3.0 - 6.4
S4	276x312	1.86 kg	1904 kgf	6-7 bar	20 mm	4.8 - 6.4	4.8 - 6.4	4.8 - 6.4



VF3

1.497 KGF

DIMENSION		SPECIFICATIONS		CLAMPING RATE	
LENGTH	276 mm	STRENGTH	1.497 kgf	STEEL	3.0 - 6.4
HEIGHT	312 mm	AIR PRESSURE	5-7 bar	ALUMINIUM	3.0 - 6.4
WEIGHT	1.70 kg	STROKE	26 mm	STAINLESS STEEL	3.0 - 6.4

Ürün	Ölçü	Ağırlık	Kuvvet	Hava Basıncı	Stroke	Çelik	Alüminyum	Paslanmaz
S1	276x270	1.10 kg	818 kgf	5-7 bar	20 mm	2.4 - 4.8	2.4 - 4.8	2.4 - 4.8
S2	276x312	1.50 kg	918 kgf	5-7 bar	20 mm	2.4 - 5.0	2.4 - 5.0	2.4 - 5.0
S3	276x312	1.70 kg	1497 kgf	5-7 bar	26 mm	3.0 - 6.4	3.0 - 6.4	3.0 - 6.4
S4	276x312	1.86 kg	1904 kgf	6-7 bar	20 mm	4.8 - 6.4	4.8 - 6.4	4.8 - 6.4