




CH-KB/SS

Countersunk Head Knurled Body Stainless Steel
Silindirik Havşa Kafa Paslanmaz






UNIT : mm

Thread	P/N	T(GRIP RANGE) Min Max	A Rer	Hole Size $+0.1$ 0	D $+0.07$ -0.1	B	K	L
M3	CH-KB/SS-0330	1.6-3.0	5.0	5.0	4.9	7.8	1.5	9.5
M3	CH-KB/SS-0340	3.0-4.0	6.0	5.0	4.9	7.8	1.5	10.5
M4	CH-KB/SS-0435	1.6-3.5	6.0	6.0	5.9	9.0	1.5	11.0
M4	CH-KB/SS-0450	3.5-5.0	8.0	6.0	5.9	9.0	1.5	13.0
M5	CH-KB/SS-0535	1.6-3.5	8.0	7.0	6.9	10.0	1.5	14.0
M5	CH-KB/SS-0550	3.5-5.0	9.0	7.0	6.9	10.0	1.5	15.0
M6	CH-KB/SS-0640	1.6-4.0	9.0	9.0	8.9	12.0	1.5	15.0
M6	CH-KB/SS-0660	4.0-6.0	11.0	9.0	8.9	12.0	1.5	17.0
M8	CH-KB/SS-0845	1.6-4.5	10.0	11.0	10.9	14.0	1.5	16.5
M8	CH-KB/SS-0860	4.5-6.0	12.5	11.0	10.9	14.0	1.5	19.0
M10	CH-KB/SS-1045	1.6-4.5	11.0	13.0	12.9	16.0	1.7	19.0
M10	CH-KB/SS-1060	4.5-6.0	12.5	13.0	12.9	16.0	1.7	20.5
M12	CH-KB/SS-1250	1.6-5.0	13.5	15.0	14.9	18.0	1.8	22.5

CH-KBC/SS

Countersunk Head Knurled Body Close End - Stainless Steel
Silindirik Havşa Kafa Sızdırmaz - Paslanmaz






UNIT : mm

Thread	P/N	T(GRIP RANGE) Min Max	A Rer	Hole Size $+0.1$ 0	D $+0.07$ -0.1	B	K	L
M4	CH-KBC/SS-0435	1.6-3.5	12.3	6.0	5.9	9.0	1.5	17.3
M5	CH-KBC/SS-0535	1.6-3.5	13.5	7.0	6.9	10.0	1.5	19.5
M6	CH-KBC/SS-0640	1.6-4.0	17.5	9.0	8.9	12.0	1.5	23.5
M8	CH-KBC/SS-0845	1.6-4.5	20.0	11.0	10.9	14.0	1.5	26.5
M10	CH-KBC/SS-1050	1.6-5.0	25.5	13.0	12.9	16.0	1.7	33.0
M12	CH-KBC/SS-1235	1.6-3.5	29.5	16.0	15.9	19.0	1.8	38.0

FH-KB/SS

Flat Head Knurled Body Stainless Steel
Silindir Flanş Kafa Paslanmaz






UNIT : mm

Thread	P/N	T(GRIP RANGE) Min Max	A Rer	Hole Size $+0.1$ 0	D $+0.07$ -0.1	B	K	L
M3	FH-KB/SS-0320	0.5-2.0	4.5	5.0	4.9	7.0	0.8	8.8
M3	FH-KB/SS-0330	2.0-3.0	6.2	5.0	4.9	7.0	0.8	10.5
M4	FH-KB/SS-0420	0.5-2.0	6.0	6.0	5.9	9.0	0.8	10.8
M4	FH-KB/SS-0440	2.0-4.0	8.0	6.0	5.9	9.0	0.8	13.0
M5	FH-KB/SS-0525	0.5-2.5	7.0	7.0	6.9	10.0	1.0	13.0
M5	FH-KB/SS-0545	2.5-4.5	9.5	7.0	6.9	10.0	1.0	15.5
M6	FH-KB/SS-0630	0.5-3.0	8.5	9.0	8.9	13.0	1.5	15.0
M6	FH-KB/SS-0650	3.0-5.0	11.0	9.0	8.9	13.0	1.5	17.5
M8	FH-KB/SS-0835	0.5-3.5	11.0	11.0	10.9	15.0	1.5	18.0
M8	FH-KB/SS-0860	3.5-6.0	14.0	11.0	10.9	15.0	1.5	21.0
M10	FH-KB/SS-1035	1.0-3.5	12.0	13.0	12.9	17.0	1.8	20.3
M10	FH-KB/SS-1055	3.5-5.5	15.7	13.0	12.9	17.0	1.8	24.0
M12(16H)	FH-KB/SS-1235	1.0-3.5	16.0	16.0	15.9	19.0	1.8	22.0
M12(16H)	FH-KB/SS-1255	3.5-5.5	18.0	16.0	15.9	19.0	1.8	24.3
M12	FH-KB/SS-1235(15H)	1.0-3.5	16.0	15.0	14.9	19.0	1.8	22.0
M12	FH-KB/SS-1255(15H)	3.5-5.5	18.0	15.0	14.9	19.0	1.8	24.3

FH-KBC/SS

Flat Head Knurled Body Close End - Stainless Steel
Silindir Flanş Kafa Sızdırmaz - Paslanmaz






UNIT : mm

Thread	P/N	T(GRIP RANGE) Min Max	A Rer	Hole Size $+0.1$ 0	D $+0.07$ -0.1	B	K	L
M4	FH-KBC/SS-0420	0.5-2.0	12.0	6.0	5.9	9.0	0.8	16.5
M4	FH-KBC/SS-0425	1.0-2.5	12.8	6.0	5.9	9.0	0.8	17.3
M5	FH-KBC/SS-0525	0.5-2.5	13.0	7.0	6.9	10.0	1.0	18.0
M5	FH-KBC/SS-0540	2.5-4.0	14.5	7.0	6.9	10.0	1.0	19.5
M6	FH-KBC/SS-0630	0.5-3.0	17.0	9.0	8.9	13.0	1.5	20.5
M6	FH-KBC/SS-0655	3.0-5.5	20.0	9.0	8.9	13.0	1.5	23.5
M8	FH-KBC/SS-0835	0.5-3.5	21.5	11.0	10.9	15.0	1.5	25.5
M8	FH-KBC/SS-0860	3.5-6.0	24.0	11.0	10.9	15.0	1.5	28.0
M10	FH-KBC/SS-1035	0.5-3.5	26.0	13.0	12.9	17.0	1.8	29.0
M10	FH-KBC/SS-1060	3.5-6.0	31.3	13.0	12.9	17.0	1.8	34.3
M12	FH-KBC/SS-1230	0.5-3.0	29.5	16.0	15.9	23.0	2.0	39.0

RH-KB/SS

Reduce Head Knurled Body Stainless Steel
 Silindirik Sıfır Kafa Paslanmaz






UNIT : mm

Thread	P/N	T(GRIP RANGE) Min Max	A Rer	Hole Size $+0.1$ 0	D $+0.07$ -0.1	B	K	L
M3	RH-KB/SS-0315	0.5-1.5	5.0	5.0	4.9	5.5	0.35	8.5
M3	RH-KB/SS-0325	1.5-2.5	6.0	5.0	4.9	5.5	0.35	9.5
M4	RH-KB/SS-0415	0.5-1.5	5.5	6.0	5.9	7.0	0.50	10.0
M4	RH-KB/SS-0425	1.5-2.5	6.5	6.0	5.9	7.0	0.50	11.0
M5	RH-KB/SS-0520	0.5-2.0	6.0	7.0	6.9	8.0	0.60	12.0
M5	RH-KB/SS-0535	2.0-3.5	7.5	7.0	6.9	8.0	0.60	13.5
M6	RH-KB/SS-0630	0.5-3.0	9.0	9.0	8.9	10.0	0.60	14.5
M6	RH-KB/SS-0645	3.0-4.5	10.5	9.0	8.9	10.0	0.60	16.0
M8	RH-KB/SS-0835	0.5-3.5	10.0	11.0	10.9	12.3	0.60	16.5
M8	RH-KB/SS-0850	3.5-5.0	11.5	11.0	10.9	12.3	0.60	18.0
M10	RH-KB/SS-1035	0.5-3.5	12.0	13.0	12.9	14.5	0.85	19.0
M12	RH-KB/SS-1235	0.5-3.5	14.5	15.0	14.9	16.5	0.85	22.5

RH-KBC/SS

Reduce Head Knurled Body Close End - Stainless Steel
 Silindirik Sıfır Kafa Sızdırmaz - Paslanmaz






UNIT : mm

Thread	P/N	T(GRIP RANGE) Min Max	A Rer	Hole Size $+0.1$ 0	D $+0.07$ -0.1	B	K	L
M4	RH-KBC/SS-0420	0.5-2.0	12.5	6.0	5.9	7.0	0.50	16.5
M5	RH-KBC/SS-0525	0.5-2.5	13.5	7.0	6.9	8.0	0.60	18.5
M6	RH-KBC/SS-0630	0.5-3.0	17.0	9.0	8.9	10.0	0.60	23.0
M8	RH-KBC/SS-0835	0.5-3.5	19.5	11.0	10.9	12.3	0.60	26.5
M10	RH-KBC/SS-1035	0.5-3.5	25.5	13.0	12.9	14.5	0.85	33.0
M12	RH-KBC/SS-1240	2.0-4.0	20.0	15.0	14.9	16.5	0.85	28.0

FH-IHB/SS

Flat Head Inner-Hex Body Stainless Steel
Yarım Altıköşe Flanş Kafa Paslanmaz






UNIT : mm

Thread	P/N	T(GRIP RANGE) Min Max	A Rer	Hole Size $+0.1$ 0	D $+0.07$ -0.1	B	K	L
M4	FH-IHB/SS-0425	0.5-2.5	6.0	6.0	5.9	9.0	0.8	10.8
M4	FH-IHB/SS-0435	2.5-3.5	8.2	6.0	5.9	9.0	0.8	13.0
M5	FH-IHB/SS-0525	0.5-2.5	8.0	7.0	6.9	10.0	1.0	13.0
M5	FH-IHB/SS-0535	2.5-3.5	9.5	7.0	6.9	10.0	1.0	14.5
M6	FH-IHB/SS-0635	0.5-3.5	9.0	9.0	8.9	13.0	1.5	15.8
M6	FH-IHB/SS-0650	3.5-5.0	12.2	9.0	8.9	13.0	1.5	19.0
M8	FH-IHB/SS-0835	0.5-3.5	11.0	11.0	10.9	15.0	1.5	18.0
M8	FH-IHB/SS-0850	3.5-5.0	12.0	11.0	10.9	15.0	1.5	19.0
M10	FH-IHB/SS-1035	0.5-3.5	12.5	13.0	12.9	17.0	1.8	20.3
M10	FH-IHB/SS-1050	3.5-5.0	14.2	13.0	12.9	17.0	1.8	22.0
M12	FH-IHB/SS-1250	2.0-5.0	16.5	16.0	15.9	23.0	2.2	27.5

FH-IHBC/SS

Flat Head Inner-Hex Body Close End Stainless Steel
Yarım Altıköşe Flanş Kafa Sızdırmaz Paslanmaz






UNIT : mm

Thread	P/N	T(GRIP RANGE) Min Max	A Rer	Hole Size $+0.1$ 0	D $+0.07$ -0.1	B	K	L
M4	FH-IHBC/SS-0420	0.5-2.0	12.5	6.0	5.9	9.0	0.8	17.3
M5	FH-IHBC/SS-0525	0.5-2.5	13.5	7.0	6.9	10.0	1.0	19.5
M6	FH-IHBC/SS-0630	0.5-3.0	17.5	9.0	8.9	13.0	1.5	24.3
M8	FH-IHBC/SS-0835	0.5-3.5	20.5	11.0	10.9	15.0	1.5	28.0
M10	FH-IHBC/SS-1035	0.5-3.5	26.5	13.0	12.9	17.0	1.8	33.0
M12	FH-IHBC/SS-1242	0.5-4.2	23.4	16.0	15.9	20.0	1.7	36.0

RHH-IHB/SS

Reduce Hex Head Inner-Hex Body Stainless Steel
 Yarım Altıköşe Sıfır Kafa Paslanmaz






UNIT: mm

Thread	P/N	T(GRIP RANGE) Min Max	A Rer	Hole Size $+0.1$ 0	D $+0.07$ -0.1	HB	K	L
M3	RHH-IHB/SS-0315	0.5-1.5	5.0	5.0	4.9	6.0	0.5	8.5
M4	RHH-IHB/SS-0420	0.5-2.0	6.0	6.0	5.9	7.0	0.6	10.0
M4	RHH-IHB/SS-0435	2.0-3.5	8.0	6.0	5.9	7.0	0.6	12.0
M5	RHH-IHB/SS-0525	0.5-2.5	7.0	7.0	6.9	8.0	0.6	12.0
M5	RHH-IHB/SS-0540	2.5-4.0	9.0	7.0	6.9	8.0	0.6	14.0
M6	RHH-IHB/SS-0630	0.5-3.0	9.0	9.0	8.9	10.0	0.6	14.5
M6	RHH-IHB/SS-0650	3.0-5.0	10.5	9.0	8.9	10.0	0.6	16.0
M8	RHH-IHB/SS-0835	0.5-3.5	10.0	11.0	10.9	12.5	0.6	16.5
M8	RHH-IHB/SS-0850	3.5-5.0	11.5	11.0	10.9	12.5	0.6	18.0
M10	RHH-IHB/SS-1035	0.5-3.5	12.5	13.0	12.9	14.3	0.85	19.0
M10	RHH-IHB/SS-1050	3.5-5.0	16.3	13.0	12.9	14.3	0.85	22.8
M12	RHH-IHB/SS-1242	0.5-4.2	14.5	16.0	15.9	17.5	0.85	23.0

RHH-IHBC/SS

Reduce Hex Head Inner-Hex Body Close End Stainless Steel
 Yarım Altıköşe Sıfır Kafa Sızdırmaz Paslanmaz



UNIT: mm

Thread	P/N	T(GRIP RANGE) Min Max	A Rer	Hole Size $+0.1$ 0	D $+0.07$ -0.1	HB	K	L
M4	RHH-IHBC/SS-0420	0.5-2.0	13.0	6.0	5.9	7.0	0.5	16.5
M5	RHH-IHBC/SS-0525	0.5-2.5	14.5	7.0	6.9	8.0	0.6	18.5
M6	RHH-IHBC/SS-0630	0.5-3.0	18.0	9.0	8.9	10.0	0.6	23.0
M8	RHH-IHBC/SS-0835	0.5-3.5	20.5	11.0	10.9	12.3	0.6	26.5
M10	RHH-IHBC/SS-1035	0.5-3.5	27.0	13.0	12.9	14.5	0.85	33.0
M12	RHH-IHBC/SS-1260	2.0-6.0	32.8	16.0	15.9	20.0	0.85	37.9